STRAPPING & SUPPLIES

POLYPROPYLENE STRAPPING

- The most inexpensive of all strapping materials
- Lightweight, easy to apply and recyclable .
- Available in both manual and machine grade • Manual application is ideal for low
- and moderate volume users
- Ideal for light duty palletizing, unitizing, carton closing and bundling



Strength Feet MACHINE GRADE

		-							
PA526	White	3/8	300	12900	1	8	8	28	
PF073	White	1/2	300	9900	1	8	8	31	
MANU	AL GRADE								
PF079	Black	5/8	500	7500	1	8	8	31	
PF067	Black	5/8	700	6000	1	8	8	31	
PF078	Black	3/4	1050	4500	1	8	8	31	
PF075	Black	1/2	600	7200	1	8	8	31	
PF071	Black	1/2	750	5600	1	16	6	40	
PF077	Black	5/8	850	6000	1	8	8	31	
PF074	Black	5/8	1100	4400	1	16	6	40	
PF083	Black	1/2	600	7200	1	16	6	31	

POLYPROPYLENE **STRAPPING W/BUCKLES**

• Hand strap large or small

- packages of all shapes Self dispensing box for convenience
- Includes 360 steel buckles •
- This unit comes factory set at 1/2" but can easily be adjusted to strap width 5/8", 1/4" or 3/8"

Model	Strap	Strength	Length'	Price
No.	Width"	Ibs.		/Each
PF072	1/2	300	3300	

EDGE PROTECTORS

These plastic edge protectors spread strapping tension across a 2" surface. Protects packages from surface damage. 1" L x 1 1/4" W.

- For use with strapping up to 3/4" W
- Quantity of 1000 per package
- Priced per package • Model No. PA497 Price/Each \$





W"

/Eacl

1/2" POLYPROPYLENE STRAPPING KITS Consists of the following components: 1- PFO71 1/2" x 5600', 750-lb strength poly strapping 1- PE555 dispenser 1- PA555 1/2" poly sealer 1- PC939 polypropylene and polyester tensioner 1- PA509 1/2" open seals, 2000/box Model No. PD023 Price/Each \$ PA509 PA555 PC939

SEMI-AUTOMATIC STRAPPING MACHINES

- Quick, efficient strapping of packages of almost any size or shape •
- Stabilized tensioning controlled electronically can be adjusted from 4.4 to 88 lbs.
- Automatically feeds, tension and heat seals the strap •
- . Few moving parts, making it easy to maintain and keep operation costs low
- Runs 5 to 15.5 mm polypropylene strapping without changing parts
- Ready to operate in 45 seconds

Specifications

Strap width: Power supply: Tension range: Dimensions: 30 3/4" W x 30 1/2" H x 21 3/8" D Weight: 88 lbs.

1/4", 3/8", 1/2", 5/8" 100-120V, 220-240V, 1 Phase 50-60 Hz up to 88 lbs.

Model No.PF082 Price/Each \$





SEALS & BUCKLES FOR POLYPROPLYLENE STRAPPING

Model No.	Strap Width"	Туре	Qty /Box	Price /Each	Steel	16 16 16
STEEL SEAL	S				Seals	
PA509	1/2	Open	2000			
PA510	5/8	Open	2000			El marti
PC886	3/4	Open	1000			
PLASTIC BL	JCKLES					
PA500	3/8	Plastic	1000		Plastic	
PA498	1/2	Plastic	2000		Buckles	
PA499	5/8	Plastic	2000			
WIRE BUCK	(LES					
PA501	1/2	Wire	2000			(And the second
PA502	1/2	H.D. Wire*	1000			
PA503	5/8	Wire	2000		Wire	
PA504	5/8	H.D. Wire*	1000		Buckles	
Note: Recom	nmended for stra	ap with strength over 4	00 lbs.			
м						SHIPPING & INSTRUMENTS, OFFI
						PACKAGING SCALES & PRODU