

# EXTENSION CORDS & OUTLETS

## OUTDOOR VINYL EXTENSION CORDS

- Designed for industrial and contractor use
- Vinyl jacket protects against rough use, chemicals, and moisture and provides added flexibility
- Molded-on and bonded plugs and connectors resist breaking



**aurora tools**

### 3-CONDUCTOR SJTW, 300 V GROUNDING

Model No.	Length'	AWG	Amps	Watts	Colour	Price /Each
<b>HEAVY-DUTY</b>						
XC482	25	14/3	15	1875	Orange	
XC483	50	14/3	15	1875	Orange	
XC484	100	14/3	13	1625	Orange	
<b>EXTRA HEAVY-DUTY</b>						
XC485	25	12/3	15	1875	Yellow	
XC486	50	12/3	15	1875	Yellow	
XC487	100	12/3	15	1875	Yellow	



XC485

## OUTDOOR VINYL TRIPLE TAP EXTENSION CORDS

- Designed for industrial and contractor use
- Vinyl jacket protects against rough use, chemicals, and moisture
- Vinyl jacket provides added flexibility
- Molded-on and bonded plugs and connectors resist breaking



**aurora tools**

### 3-CONDUCTOR SJTW, 300 V GROUNDING

Model No.	Length'	AWG	Amps	Watts	Colour	Price /Each
<b>HEAVY-DUTY</b>						
XC488	25	14/3	15	1875	Red	
XC489	50	14/3	15	1875	Red	
XC490	100	14/3	13	1625	Red	
<b>EXTRA HEAVY-DUTY</b>						
XC491	25	12/3	15	1875	Red	
XC492	50	12/3	15	1625	Red	
XC493	100	12/3	15	1625	Red	



XC491

## OUTDOOR VINYL TRIPLE TAP EXTENSION CORDS

- Designed for use by contractors and industrial personnel
- Jacket protects against rough use, chemicals, moisture, ozone and gives added flexibility at below freezing temperatures
- Molded-on and bonded vinyl plugs and connectors resist breaking or pulling off cord
- Nickel-coated brass blades resist corrosion
- **XA719, XA720, XA721** are No Overload® circuit breaker extension cords



**PRIME**


### 3-CONDUCTOR SJTW, 300 V GROUNDING

Model No.	Length'	AWG	Amps	Watts	Colour	Price /Each
<b>HEAVY-DUTY</b>						
XA719	25	14/3	15	1875	Red	
XA720	50	14/3	15	1875	Red	
XA721	100	14/3	13	1625	Red	
<b>EXTRA HEAVY-DUTY</b>						
XA722	25	12/3	15	1875	Yellow	
XA723	50	12/3	15	1875	Yellow	
XA724	100	12/3	15	1875	Yellow	



NEMA 5-15P

XA719



NEMA 5-15R

## GLACIER FLEX™ 3-OUTLET ENGINE BLOCK HEATER CORDS

- 3 conductors, SJTW -50°C, 300 V grounding
- Water-resistant
- Flame retardant
- Ultra flexible
- Nickel-coated brass blades resist corrosion
- Temperature range from -50°F to +140°F (-50°C up to +60°C)
- Primelight® indicator light flashes blue and red when power is on



**PRIME**

Model No.	Length'	AWG	Amps	Watts	Price /Each
XC730	15	16/3	13	1625	



XC730