



Omni-
Directional
Coverage



Maintenance
Free Design



Model 20V1T / 20V2T

The 20V1T is a thundering, 20HP warning siren that is a perfect fit for both large municipal and industrial applications with high ambient background noise. To make this siren an excellent choice in a wide range of applications, the 20V can be ordered in either a single tone (20V1T) or dual tone (20V2T) configuration. This is a monster!

FEATURES

Coverage Radius

Rated at 125dB(C) at 100ft*
5,000ft. estimated coverage
radius / effective range*
460 or 460/920hz
Broadcast Frequency

*Based on Sentry Siren Field Testing

Maintenance Free Continuous Duty Design

The omni-directional,
maintenance free design
ensures this siren has the
lowest operating cost in the
industry. Sentry Sirens are
rated for continuous-duty
operation in emergencies.

MADE IN USA

All Sentry Sirens are proudly
manufactured in the United
States at our Colorado
facility. Each siren is hand
built, assembled, and
thoroughly tested before
leaving our facility.

Since 1905, Sentry Siren has proudly set the standard for hand-made warning sirens in the United States and around the world.

SENTRY SIREN Inc.

Model 20V1T / 20V2T



"We are so pleased with our selection of *Sentry Siren, Inc.* as our warning system supplier. The Performance of our Sentry Siren is impressive; they are very reliable and loud. And the customer service they provided is second to none. We would highly recommend Sentry to anyone looking to invest in their community with a warning siren system."

Roger Swint - Fire Chief
City of Morrow Fire Dept. Morrow, GA

Dealer Info

 **Table Rock
Alerting Systems**
(877)-ALERT-01

KEY FEATURES

- 125dB(C) at 100' Output*
- 5,000ft estimated coverage radius at 70dB(C)*
- 20-Horsepower, Continuous-Duty AC Motor
- Available in Single or Three-Phase 208-230/460VAC
- Omni-Directional Design with True 360-Degree Coverage
- 100% Maintenance Free Design
- Electro-Mechanically Generated Sound
- 5-Year Factory Warranty
- Powder-Coated Steel Construction
- Stainless Steel Upgrade Available
- Custom Colors & Designs Available

Electrical Requirements

- **Three Phase Siren:** 20 HP: 208/230 (460V-special order), 60 Hz
NEC FLA (230V)-47.0 / 54.0 Uses Starter # S9W
- **Single Phase Siren:** 20 HP: 208/230, 60 Hz
NEC FLA (230V)-96.0 / 100.0 Uses Starter # S10W