

RANGER® ONE™ contains a proprietary rigid, fluid directing, polymer insert that is seated within the hollow-point cavity to prevent the projectile from being affected by drywall, cloth or other material which can minimize expansion and effectiveness. Upon impact, the rigid polymer insert contributes to the expansion and segmentation of the petals to ensure maximum threat-stopping energy transfer while the bonding process maintains bullet integrity and optimal penetration depth. While there are many potential threats that officers may encounter, there is only ONE cartridge that they need to confidently face them all- RANGER® ONE™.

THE ONE BULLET CHOICE FOR THOSE WHO PROTECT AND SERVE

The blue color of the bullet insert salutes our brave men and women of the Law Enforcement community, and is a visual reminder that Winchester stands behind the thin blue line, in support and appreciation, as a manufacturer.



SPECIFICATIONS

BULLET

• 147 gr Ranger Bonded Cavity Filled JHP

SHELLCASE

• 9mm Luger Nickel Plated

POWDER

· Clean burning, low flash

PRIMER

· Non-corrosive, boxer type

WATERPROOFING

 Lacquer applied to primer and waterproofing agent applied to mouth of case

VELOCITY

 1,010 fps nominal muzzle velocity when fired from a 4 inch barrel















2019 OFFERINGS

SYMBOL CARTRIDGE
RA9B1 9MM LUGER

Additional calibers currently in development

BARRIER

Bare Gelatin

Heavy Cloth

Wallboard

Plywood

Steel



Auto Glass

GRS.

Ranger ONE 9MM - 147 gr. RA9B1 Muzzle Velocity (fps)—1010



Penetration: 13" Expansion: 0.644" Retain Wt.: 99.1% Retain Wt.: 166.99 c



Penetration: 13.7" Expansion: 0.577" Retain Wt.: 99.5% Retain Wt.: 145.55 gr;



Penetration: 13.1" Expansion: 0.607" Retain Wt.: 99.5% Retain Wt.: 145.59 gr.



Penetration: 14.6" Expansion: 0.517" Retain Wt.: 99.5% Retain Wt.: 145.59 gr.



Penetration: 17.5" Expansion: 0.476" Retain Wt.: 99.4% Retain Wt.: 145.49 gr.



Penetration: 12.8" Expansion: 0.476" Retain Wt.: 67.5% Retain Wt.: 98.75 gr.