



Dear Thetford Sanitation System Purchaser:

Congratulations!

You are now the owner of one of America's finest recreational sanitation systems.

You will find, enclosed in this packet, information describing the new and unique Thermasan Waste Destruction System. Now, by simply pressing a button, you can destroy all Recreational Vehicle holding tank waste and water -- and destroy it in such a manner that is convenient, odorless and pollution-free.

The Thermasan Waste Destruction System has taken the latest chemical, biochemical and incineration techniques which are now being used by modern, pollution-free Municipal waste treatment plants and has incorporated these techniques into a mobile, safe and pollution-free waste destruction system.

To activate this system, you simply push a button on the dashboard mounted Solid State Control Panel. When your vehicle has reached a speed of approximately 25-45 miles per hour, the Thermasan System will go into action - harnessing the heretofore wasted heat energy from your engine and using it to destroy the waste and water in your holding tank.

Take a few minutes, right now, to read the enclosed literature about this truly amazing system. If you would like more information or would like to purchase the Thermasan System, simply return the enclosed postage-paid card to us.

Thank you,


James F. Janowski
Sales Manager
Thetford Corporation

JFJ/bb
Enclosure

INSTRUCTIONS--03945--ELECTRA MAGIC

A. INSTALLATION

1. Place one (1) 02125 flange seal on Slide-Ez Valve.
2. Mount unit to standard closet flange with bolt package.
3. Install base molding (two screws, one on each side).

B. ELECTRICAL HOOK UP

1. Connect directly to 12 volt DC Source as a separate circuit.
Use minimum size #14 gauge wire. (Black wire to positive (hot), white to negative (ground)).

C. INITIAL FLUSH CHARGE

1. Pour approximately three (3) gallons of water in bowl (until water reaches the charge level (c) on indicator lens). Three gallons are required for operation.
2. Add one (1) eight-ounce bottle of Aqua Kem Concentrate.

D. TO FLUSH

1. Depress flush button. (Solid state timer will give a seven (7) second flush cycle.)
2. For best results do not depress button when unit is empty.

E. EVACUATION PRIOR TO CONTINUING USE

1. Pull Slide-Ez Valve open until unit is evacuated.
2. Close Slide-Ez Valve. (Make sure valve is closed and locked.)
3. Pour approximately three (3) gallons of water in bowl (until water reaches the charge level (c) on indicator lens). Three gallons are required for operation.
4. Add one (1) eight-ounce bottle of Aqua Kem Concentrate.

F. EVACUATION PRIOR TO TEMPORARY STORAGE

1. Pull Slide-Ez Valve open until unit is evacuated.
2. Close Slide-Ez Valve. (Make sure valve is closed and locked.)
3. Refill unit to within three inches of bowl top with fresh water.
4. Add two inches (from the bottle) of Aqua Bowl Cleaner.
5. Cycle three (3) times.
6. Let stand for a few minutes for cleaning action.
7. Open Slide-Ez Valve for final evacuation.
8. Close Slide-Ez Valve. (Make sure valve is closed and locked.)
9. The unit is now ready for storage. Repeat Item C above to activate unit for use again after storage.

G. CAPACITY

Three (3) gallons charge water capacity.
Four (4) gallons waste capacity.
Seven (7) gallons total capacity.

H. WINTERIZING

1. For winter storage, evacuate unit as described in Item F.
2. For winter use, replace one half of the charge water with an approved plastic pipe anti-freeze, such as Aqua Thaw Recreational Anti-Freeze.