



Tabla de Bridas Bipartidas (Medidas en Pulgadas)

Dimensiones de Bridas DIN 2502 & VSM 18 860										Pernos de Conexión		Tornillos de la Bisagra	
DN	D	K	H	J	N	P	X	Y	Z	No. d1	d2	No. e2	PN
1"	4.25	3.11	0.55	1.77	2.50	0.079	0.47	2x45°	3.35	4-1/2"	0.59	2 – 0.39	150
1.1/4"	4.61	3.50	0.55	2.17	2.893	0.079	0.59	2x45°	3.74	4-1/2"	0.59	2 – 0.47	150
1.1/2"	5.00	3.88	0.55	2.48	4.248	0.079	0.59	2x45°	4.13	4-1/2"	0.59	2 – 0.47	150
2"	6.02	4.744	0.63	3.07	3.996	0.079	0.59	2x45°	5.12	4-5/8"	0.71	2 – 0.47	150
3"	7.48	6.00	0.71	4.13	5.255	0.079	0.59	2x45°	6.30	4-5/8"	0.71	2 – 0.47	150
4"	9.02	7.50	0.79	5.31	6.30	0.118	0.59	2x45°	7.68	4-5/8"	0.71	2 – 0.47	150
5"	10.00	8.50	1.18	6.30	7.48	0.118	0.59	2x45°	8.66	8-3/4"	0.87	2 – 0.47	150
6"	11.02	9.49	0.98	7.28	8.58	0.118	0.71	3x45°	9.84	8-3/4"	0.87	2 – 0.55	150
8"	13.50	11.73	1.10	9.45	10.75	0.118	0.71	3x45°	12.20	8-3/4"	0.87	2 – 0.55	150
10"	15.98	14.25	1.26	11.42	12.87	0.118	0.71	3x45°	14.37	12-7/8"	0.98	2 – 0.55	150
12"	19.02	17.01	1.38	13.58	15.12	0.118	0.71	3x45°	17.13	12-7/8"	0.98	2 – 0.55	150