

SmartH NVR



Key Features

- Up to 16ch IP cameras access
- Up to 8MP resolution for live view and recording
- Intelligent analysis by NVR: Intrusion (support the accurate detection of vehicle and human)
- 2 SATA hard disk, up to 12TB for each HDD
- 1 RJ45 10/100/1000Mbps network interface
- 16ch POE ports
- Smart search & playback
- Support cloud upgrade


Specification

Video Input		
IP Camera Input	16 Channel	
Incoming Bandwidth	112 Mbps	
Outgoing Bandwidth	112 Mbps	
Video Output		
HDMI Output	3840×2160,1920×1080, 1280×1024, 1024×768	
VGA Output	1920×1080, 1280×1024, 1024×768	
Decoding Capacity	1ch 8MP, 4ch 1080P, 8ch D1, 16ch D1@30fps	
Dual Stream	Support	
Multi-screen Display	1/4/9/16	
Recoding		
Resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.	
Recording Mode	Manual, Schedule (Regular, Continuous), Event	
Trigger Events	Motion Detection, Video Loss, Alarm in, IVS	
Playback and Backup		
Sync Playback	16/9/4/1	
Search Mode	Time /Date, Alarm, Picture grid, Event	
Backup Mode	USB Device, Network	
Alarm		
General Alarm	Motion Detection, Video Loss, Alarm in, Alarm out, IVS (by camera)	
Abnormal Alarm	Disk Alarm, IP Address Conflict, Network Disconnect	
Intelligent Analysis	Intrusion (support the accurate detection of vehicle and human)	
Network		
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE	
Remote Users	8 users	
Smart Phone	iPhone, iPad, Android	
Gillart i Hone		

Storage	
HDD	2 SATA ports, up to 12TB for each HDD
Interface	
Network	1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
PoE	16 Ports (IEEE802.3af), 128W
HDMI	1
VGA	1
Audio I/O	1/1
Alarm I/O	8/2
USB	3 ports (USB 2.0 × 3)
General	
Power Supply	AC100 ~ 240V
Power Consumption	< 15 W (without HDD)
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	372 × 310.5 × 46.5 mm (16.65 × 12.2 × 2.2 inch)
Net Weight	2.75 kg (6.05 lb) without HDD

Dimensions (mm)





Rear Panel

