

Smarth NVR

4CH NVR



Key Features



- Up to 4ch IP cameras access
- Up to 8MP resolution for live view and recording
- Intelligent analysis by NVR: Intrusion (support the accurate detection of vehicle and human)
- 1 SATA hard disk up to 12TB
- 1 RJ45 10/100Mbps network interface
- 4ch POE ports
- Smart search & playback
- Support cloud upgrade

Specification

| Video Input | |
|----------------------|--|
| IP Camera Input | 4 Channel |
| Incoming Bandwidth | 40 Mbps |
| Outgoing Bandwidth | 40 Mbps |
| Video Output | |
| HDMI Output | 3840×2160, 1920×1080, 1280×1024, 1024×768 |
| VGA Output | 1920×1080, 1280×1024, 1024×768 |
| Decoding Capacity | 1ch 8MP, 4ch 1080P@30fps |
| Dual Stream | Support |
| Multi-screen Display | 1/4 |
| Recoding | |
| Resolution | 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc. |
| Recording Mode | Manual, Schedule (Regular, Continuous), Event |
| Trigger Events | Motion Detection, Video Loss, Alarm in, IVS |
| Playback and Backup | |
| Sync Playback | 4/1 |
| Search Mode | Time /Date, Alarm, Picture grid, Event |
| Backup Mode | USB Device, Network |
| Alarm | |
| General Alarm | Motion Detection, Video Loss, Alarm in, Alarm out, IVS (by camera) |
| Abnormal Alarm | Disk Alarm, IP Address Conflict, Network Disconnect |
| Intelligent Analysis | Intrusion detection (support the accurate detection of vehicle and human) by NVR |
| Network | |
| Network Function | HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE |
| Remote Users | 8 users |
| Smart Phone | iPhone, iPad, Android |
| Interoperability | ONVIF, SDK, CGI |

| Storage | |
|----------------------|--|
| HDD | 1 SATA Ports, up to 12TB for each HDD |
| Interface | |
| Network | 1 × RJ-45, 10/100 Mbps self-adaptive Ethernet port |
| PoE | 4 Ports (IEEE 802.3af), 32W |
| HDMI | 1 |
| VGA | 1 |
| Audio I/O | 1/1 |
| Alarm I/O | 4/1 |
| USB | 3 ports (USB 2.0 × 3) |
| General | |
| Power Supply | DC48V/1.25A |
| Power Consumption | < 15 W (without HDD) |
| Operating Conditions | -10 °C ~ 50 °C (14 °F ~ 122 °F) |
| Storage Conditions | Less than 90% RH |
| Certifications | CE/FCC |
| Dimensions | 255 × 235.1 × 47.5 mm (10.04" × 9.26" × 1.87") |
| Net Weight | 0.9 kg (1.98 lb) without HDD |

Dimensions (mm)



Rear Panel

