



Set Up Router



The router supports the 2.4GHz WiFi (doesn't support the 5GHz), and is connected to the WiFi network. Please set the parameters of the router before connecting the WiFi network, and record the SSID and password of your WiFi.

Smart Bulb Instructions

Parameter:

Special feature:Dimmable, Color_changingLight type:LEDWattage:9 wattsLight colour:MulticolorController type:Google Assistant, Amazon AlexaBulb base:E26Light source wattage:9 Watts



Ready to work Manually add Wi-Fi devices in EZ mode



Step1:Power on the device.

Step2:Switch the device on ,off,on,off and on.

Step3:Confirm that the indicator blinks quickly.

Install Free App

Download APP: scan the QR code below to download and install. Register and login: open the "MySmartH" APP to register and login according to the prompts.



Customer Support



Two pairing modes are provided in the MySmartH app. The Wi-Fi Easy Connect (EZ) mode is the default mode, and the access point (AP) mode is the compatible mode. The user can tap the pairing mode drop-down list in the top-right corner of the page to switch between the pairing modes.

Manually add Wi-Fi devices in EZ mode

00:24 🕇	.ıl 🕈 🕢		23:16 <i>4</i>			
Model Home ~	•		<	Add Manually	Auto Scan	Э
Light Sho	owers		Home Safety			
4 °C Excellent Outdoor Temp. Outdoor PM2.5	91.0 % Outdoor Humidity		Video Surveillance	Light Sourc (Wi-F"	rip Lights Vi-Fi)	PIR Light (Wi-Fi)
Home	Away		Smart Door Lock			
		2	Lighting System	Ceiling light (Wi-Fi)		
All Devices Living Room	Master Bedroom Of ••••		Electrical Engineering			
	ALARM SYSTEM 0 0 0		Home Appliance			
Smart Socket Office V	Alarm System Family Room		Home Gateway			
▲ 11-19 11:25	0		Pet			
Smart Lock Front Door	Front Door		Exercise&He alth			
NVR	▲ 11-18 14:47		Water Meter Monitoring			
NVR-Recording Basement	Garage Door Garage					
	(III					
Home Sma). O					
-						

1. Open "MySmartH" APP, press the'+' in the upper right comer of the main screen;

2. Choose "Lighting System", click "Light Source".

17:34 🕇		23:20 🕇	
Cancel		Cancel	$EZ\;Mode\leftrightarrows$
Select 2.4 GHz Wi-Fi Network and enter password. If your Wi-Fi is 5GHz, please set it to be 2.4GHz. Common router setting method		Reset the device find the light is blinking rapidly, (1) Power on the device; (2) Turn on-off-on-off-on (S (3) Ensure the light is blinking Note: please complete the minutes after resetting the o	irst. , pls skip the reset step: subject to the user manual); g rapidly; network districution within 3 device.
✓ Wi-Fi - 2.4Ghz		① ② 0n/0ff ×3	3
 ? ? 27shadow 	<u>ل</u>	Perform net pairing a	as prompted. >
Next	3	Confirm the light	nt is blinking rapidly; ext

- 3. Choose WiFi and enter password and tap "Next";
- 4. Confirm the light is blinking rapidly and tap"Next";



5. Tap "Done";





Now your Smart Bulb is successfully added to MySmartH app.



Manually add Wi-Fi devices in AP mode

If the connection fails, please try AP mode

If a dual-band network that supports both 2.4 GHz and 5 GHz bands is used, the AP mode can be used to add devices.

In AP mode, follow the instructions to enable the indicator to blink slowly, select Confirm the indicator is blinking slowly, and then tap Next.



Ready to work Manually add Wi-Fi devices in AP mode



Step1:Power on the device.

Step2: Switch the device on ,off,on,off and on.

Step3: Confirm that the indicator blinks quickly.

Step4: After the indicator blinks rapidly, repeat the operation(Switch the device on ,off,on,off and on)

Step5: Confirm the light is blinking slowly;

Connect the Smart Bulb to MySmartH App



1. Open "MySmartH" APP, press the'+' in the upper right comer of the main screen;

2. Choose "Lighting System", click "Light Source".

17:34 🕇		23:39 🗗	. 11 🗢
Cancel		Cancel	4 AP Mode \Rightarrow
Select 2.4 GHz Wi-Fi enter passw If your Wi-Fi is 5GHz, please Common router settion × Wi-Fi - 5Ghz ✓ Wi-Fi - 2.4Ghz	Network and yord. set it to be 2.4GHz. ng method	Reset the device first If the light is blinking slowly, pl ① Power on the device; ② Switch 'on-off-on-off-on'. , rapidly, switch 'on-off-on-off-on user manual); ③ Ensure that the light is blink Note: please complete the net minutes after resetting the devi	st. s skip the reset step: After the light is blinking on' again (Subject to the ing slowly; work districution within 3 <i>v</i> ice.
27shadow	4	① ② On/Off ×3 … On/Off ×3	3 *
A 12345	<u>ی</u>	Perform net pairing as	prompted. >
Next	3	Confirm the light	is blinking slowly; t

- 3. Choose WiFi and enter password and Tap "Next";
- 4. Tap"AP Mode"in upper right screen;

23:39 7	I ? 1	21:12 √ < MySmartH		.ıl 🗢 🚱
Cancel		Settings	Wi-Fi	
Connect your mobile phone to the		\\/i_Ei		
device's hotspot		VVI-1 1		
shown below.		27shadow		🔒 🤶 🚺
<pre> Settings WLAN </pre>				
		MY NETWORKS		
WLAN		office ap		🔒 🤶 🚺
SmartLife-XXXX	6	SmartLife-1DD)4	? (j)
Wifi - Guest 🗢	(i)	Veriified L 2.4	<u>^</u>	
Wifi - Home 🔒 🗢		venimedH_2.4	G	
2. Go back to the app and continue to add devices.		OTHER NETWORKS	212	
Local Network AccessDevice might not to be connected if the access if not ena	be able Ibled.	csgn_rogers		🔒 🤶 🚺
		Other		
		Ask to Join Netw	vorks	Ask >
Go to Connect	5	Known networks wil known networks are before joining a new	ll be joined automa available, you wil network.	atically. If no I be asked
		Auto-Join Hotsp	ot As	sk to Join >
		Allow this device to	automatically disc	cover nearby

5. Tap "Go to Connect";

6. Click"SmartLife-1DD4";

In AP mode, on the Wi-Fi setting page of the mobile phone, find the Wi-Fi hotspot starting with SmartLife.



7. Tap the Wi-Fi hotspot to connect the mobile phone to it.

8.After a successful connection, go back to the app to start pairing.

00:24 🕇	. II 🗢 🚺	00:24 🕇	. II 奈 [∱]
Cancel			9 Done
Adding de Ensure that the devic	evice te is powered on.	Added.	
		Device added successf	ully
		Living Room Master Bedr	oom Office Garage Basement
		Front Door Family Room	
C			
01:25	9		
Scan Registe devices. on Clou	er Initialize Id. the device.		
	_		

The device pairing page on the app appears again and the pairing process continues.

9. Tap "Done"





Now your Smart Bulb is successfully added to MySmartH app.

