

# **Smart Lock Operation Instructions**



#### 1. Set Administrator Password

- 1.1. Wake up the touch button, and see the button light illuminate.
- 1.2. Enter the number "1", and then press the "#" key.
- 2.3. Enter the specified password and press "#" to confirm. For example, enter "181818" and press "#" (Password is 6 ~ 12 digits). Please note that the entered password cannot be "123456".
- 2.4. Enter the password again and press "#" to confirm.

## 2. Add Cards

- 2.1. Wake up the touch button, and see the button light illuminate.
- 2.2. Enter the number "2" and press "#".
- 2.3. Enter the administrator password (Device Security Key) and press "#".
- 2.4. Place the card in the sensing area, and the system will prompt "Operation succeeded".

## 3. Add Fingerprints

3.1. Wake up the touch button, and see the button light illuminate.

3.2. Enter the number "3" and press "#".

3.3. Enter the administrator password (Device Security Key) and press "#". The system will prompt "Please press your finger".

3.4. Enter the fingerprint according to the system prompt, and the system will prompt "Operation succeeded" after completion.

## 4. Configure Network

4.1. Search and download the "MySmartH" mobile APP in the mobile phone application market, and create an account.

4.2. Enter the number "4" and then press "#".

4.3. Enter the administrator password (Device Security Key) and press "#". The system will prompt "Configure network".

4.4 Open the "MySmartH" mobile app and follow the steps below:

Add Device  $\rightarrow$  Security&Sensors  $\rightarrow$  Lock(Wi-Fi)  $\rightarrow$  Enter Wi-Fi password  $\rightarrow$  Confirm indicator rapidly blink  $\rightarrow$  Adding device. At last, wait for the connection to succeed.

		22:08 7	<b>.</b> ∥?∎	22:08 🕫			.⊪≎∎)
(		George Home 🛩	<u>o</u> 🕂	<	Add Manually	Auto Scan	Ξ
		->Clear		Electrical Engineering			SOS
ł		18 °C 71 % Outdoor Temperature Outdoor Humidi	990.9 hPa Outdoor Air Pressure	Lighting	Garage Door Opener	Alarm (Wi+Ei)	Emergency Button (ZigBee)
1		🚺 Disarm	🔥 Arm	Large Home Appliance		_	L
ł				Small Home Appliance	Lock (Wi-Fi)	Lock (BLE)	Temperature and Humidity Sensor (Wi-Fi)
		All Devices living room M	aster bedroom 🛛 😁	Kitchen Appliance			
I	SMARTH Hame Automation-	ALEW SYSTEM 99-23 12:28		Sceurity & Sensor	Temperature and Humidity Sensor (ZigBee)	Contact Sensor (ZigBee)	Contact Sensor (Wi-Fi)
		George ALarm System G Kitchen G	arage Door (mini) arage	Video Surveillance		*	*
I			09-23 21:50	Exercise&H ealth	Motion Detector (ZigBee)	Smoke Detector (Wi-Fi)	Smoke Detector (ZigBee)
	<b>20.000</b> <sup>+</sup> umme	Basement Camera S Basement G	MART LOCK arage	Pet	٥	٥	СО
I	REGISTERED		-	Others	Flood Detector (Wi-Fi)	Flood Detector (ZigBee)	CO Detector (ZigBee)
I		Door Bell S	mart Valve		*		
	Siri Google Assistant 🔊 Siri O alexa III 小度				Sensor (Wi-Fi)	Safe Box (Wi-Fi)	
		©OFF					
1		Home - Q- Smart	Me				



## **Restore Factory Settings**

1.1. Remove the battery cover on the rear lock surface, and press the "Reset" button for 3 seconds until the voice prompts "System initialization, please press the confirm button".

1.2. Release the button and press the "#" key in the password input area to confirm.

1.3. The voice prompts "Operation succeeded", and all data of the system is cleared. The administrator password is restored to "123456".

**Warning:** After restoring the factory settings, the smart lock added through the mobile APP can no longer be managed and configured by the mobile APP, please use it with caution!