

# TSC

The Smarter Choice.



## TX200 SERIES – Desktop Thermal Transfer Bar Code Printer HIGH PERFORMANCE FOR A NEW GENERATION



### KEY FEATURES

- Up to 203 mm (8") per sec. print speed
- 128 MB Flash memory and 128 MB SDRAM memory
- MicroSD Flash memory expansion up to 32 GB
- User-friendly clamshell design
- Serial, internal Ethernet USB 2.0 & USB host interfaces standard
- 3.5" color TFT Display (Standard for TX600, Optional for TX200 & TX300)
- Label capacity up to 127 mm (5") OD
- Ribbon capacity up to 300 m (984')
- TSPL-EZ™ firmware for plug-n-play ease
- Optional peel-off module, cutter module, external Bluetooth module, slot-in 802.11 a/b/g/n wireless module, stand-alone keyboard
- ENERGY STAR® qualified

### APPLICATIONS

- Business/Office
- Product Marking
- Compliance Labeling
- Asset Tracking
- Document Management
- Shelf-Labeling
- Shipping/Receiving
- Specimen Labeling
- Inventory Control
- Patient Tracking

### GENERAL INDUSTRY

- Manufacturing
- Warehouse & Logistics
- Healthcare
- Custom Signage

Contact us for pricing or a lable free printer audit  
Cloud Printing Solutions Ltd  
0161 818 6446  
[www.cloudprintingsolutionsltd.com](http://www.cloudprintingsolutionsltd.com)



# TX200 SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TX200	TX300	TX600
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	24 dots/mm (600 DPI)
Printing method	Thermal Transfer & Direct Thermal		
Max. print speed	203 mm (8")/second	152 mm (6")/second	102 mm (4")/second
Max. print width	108 mm (4.25")	106 mm (4.17")	106 mm (4.17")
Max. print length	25,400 mm (1,000")	11,430 mm (450")	2,540 mm (100")
Enclosure	Clamshell with double-walled plastic		
Physical dimension	226mm (W)x198mm (H)x332mm (D) 8.90" (W)x7.80" (H)x13.07" (D)		226 mm (W) x 200 mm (H) x 332 mm (D) 8.90" (W) x 7.87" (H) x 13.07" (D)
Weight	3.75 kg (8.27 lbs)		4.08 kg ( 8.99 lbs)
Label roll capacity	127 mm (5") OD		
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside)		
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")		
Processor	32-bit RISC CPU		
Memory	<ul style="list-style-type: none"> <li>• 128 MB Flash memory</li> <li>• 128 MB SDRAM</li> <li>• microSD card reader for Flash memory expansion, up to 32 GB</li> <li>• USB 2.0</li> <li>• RS-232</li> </ul>		
Interface	<ul style="list-style-type: none"> <li>• Internal Ethernet, 10/100Mbps</li> <li>• USB Host</li> <li>• Centronics (factory option)</li> <li>• External Bluetooth (user option)</li> <li>• Slot-in 802.11 a/b/g/n wireless (dealer option)</li> </ul>		
Operation switch, button, LED/LCD	<ul style="list-style-type: none"> <li>• 1 powerswitch</li> <li>• 1 feed/pause button</li> <li>• LED panel with 8 big icons</li> </ul>	<ul style="list-style-type: none"> <li>• 1 power switch</li> <li>• 6 operation buttons (menu, feed/pause, up, down, left, right)</li> <li>• 3.5" color TFT display, 320 x 240 pixel</li> </ul>	
Power	External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 3.75A, 90W	External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 5.41A, 130W	
Sensors	<ul style="list-style-type: none"> <li>• Transmissive gap sensor</li> <li>• Black mark reflective sensor (position adjustable)</li> <li>• Ribbon encode sensor</li> <li>• Head open sensor</li> </ul>	<ul style="list-style-type: none"> <li>• Transmissive gap sensor</li> <li>• Black mark reflective sensor (position adjustable)</li> <li>• Ribbon end sensor</li> <li>• Ribbon encode sensor</li> <li>• Head open sensor</li> </ul>	
Real time clock	Factory Option	Standard	
Internal fonts	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> <li>• 1D barcode</li> </ul>		
Bar code	Code 39, Code 93, Code 128 UCC, Code 128 subsets A.B.C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF 14, EAN 14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS		
Font and barcode rotation	TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)		
Printer language	0, 90, 180, 270 degree TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)		
Media type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)		
Media width	19 ~ 112 mm (0.75" ~ 4.4")		
Media thickness	0.055 ~ 0.254 mm (2.17 ~ 10 mil)		
Media core diameter	25.4 ~ 38.1 mm (1" ~ 1.5")		
Label length	3 ~ 25,400 mm (0.1" ~ 1,000") : 3 ~ 11,430 mm (0.1" ~ 450") : 3 ~ 2,540 mm (0.1" ~ 100")		
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing		
Safety regulation	Storage: -40 ~ 60°C, 10 ~ 90% non-condensing		
Environmental concern	FCC Class B, CE Class B, RCM, UL, cUL, TÜV/Safety, CCC, BIS, EAC, ENERGY STAR® Comply with RoHS, WEEE		
Accessories	<ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• Quick start guide</li> <li>• USB cable</li> <li>• Power cord</li> <li>• External universal switching power supply</li> </ul>		
Limited warranty	<ul style="list-style-type: none"> <li>• Printer: 2 years</li> <li>• Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>• Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>		
Factory options	<ul style="list-style-type: none"> <li>• Centronics parallel interface</li> <li>• Real time clock</li> <li>• 3.5" color TFT display (includes real time clock)</li> <li>• Ribbon end sensor</li> </ul>	<ul style="list-style-type: none"> <li>• Centronics parallel interface</li> </ul>	
Dealer options	<ul style="list-style-type: none"> <li>• Peel-off module</li> <li>• Guillotine cutter (full cut)</li> <li>• 802.11 a/b/g/n wireless module (slot-in)</li> </ul>		



- CORPORATE HEADQUARTERS**  
**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 2 2218 6789  
 E-mail: apac\_sales@tscprinters.com
- LI ZE PLANT**  
**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 3 990 6677  
 E-mail: apac\_sales@tscprinters.com
- AMERICAS**  
**TSC Auto ID Technology America Inc.**  
 Tel: +1 657 258 0808  
 E-mail: americas\_sales@tscprinters.com
- MEXICO**  
**TSC Mexico Representative Office**  
 Tel: +52 (33) 3836 6682  
 E-mail: americas\_sales@tscprinters.com
- BRAZIL**  
**TSC Brazil Representative Office**  
 Tel: +55 (11) 9597 8098  
 E-mail: americas\_sales@tscprinters.com
- EMEA**  
**TSC Auto ID Technology EMEA GmbH**  
 Tel: +49 (0) 8106 37979 00  
 E-mail: emea\_sales@tscprinters.com
- RUSSIA**  
**TSC Auto ID Technology EMEA GmbH**  
 Tel: +7 495 249 9017  
 E-mail: emea\_sales@tscprinters.com
- MIDDLE EAST**  
**TSC Auto ID Technology ME Ltd, FZE**  
 Tel: +971 4 2533 069  
 E-mail: emea\_sales@tscprinters.com
- ASIA PACIFIC**  
**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 2 2218 6789  
 E-mail: apac\_sales@tscprinters.com
- CHINA**  
**Tianjin TSC Auto ID Technology Co., Ltd.**  
 Tel: +86 22 5981 6661  
 E-mail: apac\_sales@tscprinters.com

Cloud Printing Solutions Ltd  
 0161 818 6446  
[www.cloudprintingsolutionsltd.com](http://www.cloudprintingsolutionsltd.com)

