



## PRODUCT DATA SHEET

### 2 STROKE ENGINE OIL (2T)

#### API: TC , JASO: FD

**Petro Gold tow Stroke Engine oil** is manufactured from 100% virgin base oil high quality and carefully selected additives to deliver premium protection and performance. This high-performance oil is formulated for all two-stroke gasoline engines that require JASO FD-level performance lubricants, ensuring optimal engine efficiency and longevity. This is Suitable for use in both air-cooled and water-cooled two-stroke motorcycle engines. It Provides excellent lubricity characteristics, reducing wear and extending engine life.

**Petro Gold tow Stroke Engine oil** is formulated for ultra-clean burning, producing minimal smoke and carbon buildup.

#### Typical test results

Parameter	Test Method	Unit	Result
Density @15 deg. C	ASTM D4052	g/ml	0.8870
Kinematic Viscosity @ 100 °c	ASTM D445	Cst	11
Kinematic Viscosity @ 40 °c	ASTM D445	Cst	98
Viscosity Index	ASTM D2270	-	96
Pour Point	ASTM D 97	°C	-12
Flash Point	ASTM D 92	°C	246
TBN	ASTM D 2896	mg KOH/g	2.1



Petro Gold Lubricants and Grease Industry LLC, United Arab Emirates  
[info@petrogoldlub.com](mailto:info@petrogoldlub.com) [www.petrogoldlub.com](http://www.petrogoldlub.com)