



PRODUCT DATA SHEET

PETROL ENGINE OIL SAE 10W40, API: SN

Petro gold Petrol Engine oil SAE10W40 SEMI- SYNTHETIC Equivalent to API SN is a multigrade oil. Super High Performance with mineral and synthetic basis. It provides safe engine combustion at extreme loads and perfect protection from the components wear-out and corrosion provides easy cold start. Good detergent and dispersive properties provide perfect cleanliness and safe lubrication of the engine components. Developed for the most recent requirements of gasoline passenger engines. It meets all current industry standard requirements of car makers recommending 10W40 API SN.

Typical test results

Parameter	Test Method	Unit	Result
Density @15 deg. C	ASTM D4052	g/ml	0.861
Kinematic Viscosity @ 100 °c	ASTM D445	Cst	14.2
Kinematic Viscosity @ 40 °c	ASTM D445	Cst	97
Viscosity Index	ASTM D2270	-	150
Pour Point	ASTM D 97	°C	-33
Flash Point	ASTM D 92	°C	212
CCS Viscosity (-25°c)	ASTM D 5293	cP	6200
Sulfated Ash	ASTM D 874	%	0.51
TBN	ASTM D 2896	Mg KOH/g	8.5

Benefits:

- Provides long service intervals and trouble-free operation.
- Enhance protection against wear and Excellent resistance to oxidation.
- Helps reduce harmful emissions.
- Prolongs engine life and increases fuel efficiency.
- Good anti-foaming characteristic.



Petro Gold Lubricants and Grease Industry LLC, United Arab Emirates
info@petrogoldlub.com www.petrogoldlub.com