



## PRODUCT DATA SHEET

### ANTIFREEZE COOLANT

**Petro Gold Antifreeze Coolant** is a long life, fully formulated, ethylene glycol-based fluid suitable for passenger cars, light trucks and heavy-duty vehicles. The formulation is designed for both gasoline and diesel engines, its lower-silicate, reduced pH, phosphate free European technology protects all cooling against rust in all seasons. Antifreeze Coolant contains deposit control additives for protection from hard water sediments. **Petro Gold Antifreeze Coolants** are recommended for use in liquid cooling systems of gasoline and diesel engines. They are available in various concentrations. It provides ideal cooling, effective protection against corrosion and scale deposit formation in the cooling systems year-round, resulting in longer life radiator.

#### Typical test results

Parameter	Test Method	Unit	33%	50%	100%
Appearance	Visual	--	Bright & Clear	Bright & Clear	Bright & Clear
Colour	Visual	--	Green	Green	Green
Density @ 20 deg. C	ASTM D 1298	gm/cc	1.05	1.07	1.11
pH (33%)	ASTM D 1287	--	8.3	8.2	8.4
Freezing Protection (50%)	ASTM D 1177	Deg. C	-20	-42	-34
Reserved Alkalinity	ASTM D 1121	MI	1.1	1.3	3.8



Petro Gold Lubricants and Grease Industry LLC, United Arab Emirates

[info@petogold.com](mailto:info@petogold.com)

[www.petrogoldlub.com](http://www.petrogoldlub.com)