



PRODUCT DATA SHEET

PETROL ENGINE OIL

SAE 20W50 , API: SL

Petro gold Petrol Engine oil SAE 20W50 is multi-grade motor oil Equivalent to API SL, manufactured from 100% virgin base oil high quality and carefully selected additives. Suitable for use in high performance engine.

The higher viscosity grades are suitable for use in petrol engines where the viscosity and performance level is appropriate.

It recommended for use in petrol engines of passenger cars, vans, SUVs and light trucks running under both normal and harsh driving conditions.

Typical test results

Parameter	Test Method	Unit	Result
Density @ 15 deg. C	ASTM D4052	g/ml	0.893
Kinematic Viscosity @ 100 °c	ASTM D445	Cst	19
Kinematic Viscosity @ 40 °c	ASTM D445	Cst	170
Viscosity Index	ASTM D2270	-	126
Pour Point	ASTM D 97	°C	-27
Flash Point	ASTM D 92	°C	248
CCS Viscosity	ASTM D 5293	cP	8800
Sulfated Ash	ASTM D 874	%	0.55
TBN	ASTM D 2896	Mg KOH/g	8.5

Benefits:

- No loss of viscosity due to shear.
- Protection against wear and anti-oxidancy required.
- Classic and modern, It provides good detergency and high level of anti-wear additives.

