



PRODUCT DATA SHEET

DIESEL ENGINE OIL **SAE 15W40, API: CI-4**

Petro Gold DIESEL Engine oil SAE 15W40 Equivalent to API CI-4 is a multi-grade oil, manufactured from 100% virgin base oil high quality and carefully selected low ash additives that provide significantly improved resistance to wear, deposits and oxidation. It is high performance multi-grade shear-stable heavy duty diesel engine oil, developed primarily for high output naturally aspirated or turbo charged diesel engines, operating under severe conditions in on-highway and off-highway applications.

Typical test results

Parameter	Test Method	Unit	Result
Density @15 deg. C	ASTM D4052	g/ml	0.876
Kinematic Viscosity @ 100 °C	ASTM D445	Cst	14.3
Kinematic Viscosity @ 40 °C	ASTM D445	Cst	105
Viscosity Index	ASTM D2270	-	135
Pour Point	ASTM D 97	°C	33-
Flash Point	ASTM D 92	°C	230
CCS Viscosity	ASTM D 5293	cP	6400)
TBN	ASTM D 2896	Mg KOH/g	11

Benefits:

- Provides long service intervals and trouble-free operation.
- Prolongs engine life and increases fuel efficiency.
- Enhance protection against wear.

