## W01781 Specifications

| EPA (49 STATES) YES                  |
|--------------------------------------|
| CARB (50 STATES) YES                 |
| cETL (CANADA)<br>YES                 |
| Running (RATED) Watts – Gas<br>1700  |
| Starting (SURGE) Watts – Gas<br>2100 |
| AC Voltage (VOLTS) 120               |
| Frequency (Hz) 60                    |
| Engine Displacement (cc)<br>80       |
| Recoil Start<br>YES                  |
| Low Oil Shut Off<br>YES              |
| Power Stream Alternator<br>YES       |
| Cast Iron Sleeve<br>YES              |
| Fuel<br>Gas                          |

| Excitation System  Magnet                   |
|---|
| THD@Full Load<br>≤3%                        |
| Runtime @ 25% LOAD 9                        |
| 5-20R 120V 20A Duplex<br>1                  |
| USB Outlet(5V 2.1A) 1                       |
| DC Outlet 12V/TYPE  1x Lighter Style        |
| Parallel Port<br>YES                        |
| Outlet Cover<br>YES                         |
| Engine ON/OFF Switch YES                    |
| Phoenix Fat Head Block<br>YES               |
| YES   |
| Power/Low Oil/Overload Indicator Lights YES |
| Tank Size (Gallon/Litre) 0.9/3.4            |
| Steel/Plastic                               |

Plastic

| Fuel Efficient Economy Mode<br>YES                      |  |  |
|---|--|--|
| Wheel(Size/Type/Color) 5.0" -Yellow -Plastic -Flat Free |  |  |
| <b>Handle</b><br>U Shape Folding Handle                 |  |  |
| Foot Bracket<br>4xRubber Isolator                       |  |  |
| USDA FS Certified Spark Arrester<br>YES                 |  |  |
| ACCESSORIES   |  |  |
| Engine Oil (Bottle)<br>YES                              |  |  |
| Oil Funnel<br>YES                                       |  |  |
| <b>Tool Kit</b> SP wrench – Screw Driver                |  |  |
| <b>12V Battery Cable</b><br>YES                         |  |  |
| Digital Automatic Voltage Regulator<br>YES              |  |  |