W03082 Specifications

YES

| EPA (49 STATES) YES | |
|--------------------------------------|--|
| CARB (50 STATES) YES | |
| cETL (CANADA) YES | |
| Running (RATED) Watts – Gas 3000 | |
| Starting (SURGE) Watts – Gas 3300 | |
| AC Voltage (VOLTS) 120 | |
| Frequency (Hz) 60 | |
| Engine Displacement (cc) 171 | |
| Recoil Start YES | |
| Electric Start YES | |
| Low Oil Shut Off YES | |
| Power Stream Alternator YES | |
| Cast Iron Sleeve | |

| Fuel Gas | |
|--|--|
| Excitation System Magnet | |
| THD@Full Load ≤3% | |
| Runtime @ 25% LOAD 9 | |
| CONTROL PANEL | |
| 5-20R 120V 20A Duplex | |
| TT-30R 120V 30A RV | |
| USB Outlet(5V 2.1A) 1 | |
| DC Outlet 12V/TYPE 1×2 Prong Angled | |
| Charging Port for Battery YES | |
| Parallel Port YES | |
| Outlet Cover YES | |
| Engine ON/OFF Switch YES (Push Button) | |
| Phoenix Fat Head Block YES | |

| Idle Control Switch YES | |
|---|--|
| Power/Low Oil/Overload Indicator Lights YES | |
| Tank Size (Gallon/Litre) 1.8/6.8 | |
| Steel/Plastic Steel | |
| Fuel Efficient Economy Mode YES | |
| Wheel(Size/Type/Color) 5.0" -Yellow -Plastic -Flat Free | |
| Handle U Shape Folding Handle | |
| Foot Bracket 2xRubber Isolator | |
| USDA FS Certified Spark Arrester YES | |
| ACCESSORIES | |
| Engine Oil (Bottle) YES | |
| Oil Funnel YES | |
| Tool Kit SP wrench – Screw Driver | |
| 12V Battery Cable | |

YES

Volt Lock Automatic Voltage Regulator

YES

Floater Charger for Battery

YES

Quick Oil Drain

YES