

# H05754 Specifications

## EPA (49 STATES)

YES

---

## cETL (CANADA)

YES

---

## Running (RATED) Watts – Gas

5700

---

## Starting (SURGE) Watts – Gas

7125

---

## Running (RATED) Watts – LP

5700

---

## Starting (SURGE) Watts – LP

7125

---

## AC Voltage (VOLTS)

120/240

---

## Frequency (Hz)

60

---

## Engine Displacement (cc)

439

---

## Recoil Start

YES

---

## Low Oil Shut Off

YES

---

## Power Stream Alternator

YES

---

## Cast Iron Sleeve

YES

---

**Fuel**Gas / LPG

---

---

**Propane Hose**5.5ft

---

---

**Excitation System**Brushed

---

---

**THD@Full Load**25

---

---

**Runtime @ 50% LOAD**13

---

---

**5-20R 120V 20A Duplex**2

---

---

**L5-30R 120V 30A Twistlock**1

---

---

**L14-30R 120V/240V 30A Twistlock**1

---

---

**Outlet Cover**YES

---

---

**Phoenix Fat Head Block**YES

---

---

**Fuel Selector**YES

---

---

**Tank Size (Gallon/Litre)**8.0/30.0

---

---

**Steel/Plastic**Steel

---

---

**Fuel Gauge on Cap**

YES

---

**Wheel(Size/Type/Color)**

10.0" -Black -Plastic -Flat Free

---

**Handle**

U-Shaped Padded Handle w/ Grip

---

**Foot Bracket**

Hat Shape w/ 2xRubber Isolator

---

**USDA FS Certified Spark Arrester**

YES

---

**Engine Oil (Bottle)**

YES

---

**Oil Funnel**

YES

---

**Tool Kit**

SP wrench – 2xOpen Wrench 10×12

---

**LPG Regulator (1.5m)**

YES

---

**Volt Lock Automatic Voltage Regulator (AVR)**

YES

---