



**Wastewater Inflow Abatement  
Technologies & Services**



## INFLOW DEFENDER® TECHNICAL SHEET

The Inflow Defender®, inflow dish was designed to significantly prevent rain/stormwater from entering the sanitary sewer system through the manhole cover and upper frame area. The Inflow Defender® inflow dish is part of Utility Sealing Services complete "AIM" Annual Inflow & Infiltration Maintenance Program.



### Features:

- Effectively blocks abrasive debris
- Eliminates excess flow
- Fully assembled - no special tools required
- High-density Polyethylene
- Molded Structural Ribs
- Neoprene Gasket


### Benefits:

- Reduces maintenance costs
- Eliminates Motor Run-time Spikes, significantly reduces sewerage treatment costs
- Custom sized - installs quickly & easily
- Impact resistant; Long lasting; Resists Heat & Cold
- Prevents Dish from Falling Into Manhole

### Installation Procedures

- 1) Remove the manhole cover
- 2) Clean the manhole flange area of dirt and debris to ensure accurate measurement
- 3) Locate manhole frame Inside Diameter (ID) and measure across ID with a minimum of two dimensional readings for accuracy-record the smallest measurement to the nearest 1/8"
- 4) Locate manhole frame Outside Diameter (OD) and measure across OD with a minimum of two dimensional readings for accuracy-record the smallest measurement to the nearest 1/8".

**For additional assistance contact USSSI**



LIMITED WARRANTY NOTICE Every reasonable effort is made to apply USSSI's exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, USSSI MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and USSSI shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within five (5) years from date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. This information and all other further technical advice are based on USSSI's present knowledge and experience. However, USSSI assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third-party intellectual property rights, especially patent rights. In particular, USSSI disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. USSSI SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. USSSI reserves the right to make any changes according to technical progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. For professional use only -Not for sale to or use by the general public. See Inflow Defender™ Specification Sheet for complete Inflow Dish technical data.

# Inflow Defender<sup>®</sup>

## Specification Sheet



### General Description

The USSSI Manhole Inflow Defender<sup>®</sup> (Inflow Dish) was designed to significantly abate rainfall "Inflow" from entering the sanitary sewer system through the manhole cover and upper frame area. Inflow Dish shall withstand all gases associated with waste water collection systems.

### Inflow Dish Body

The inflow dish body shall be manufactured from high density polyethylene material, comply with UL Standard, 94-HB, and meet all associated ASTM specifications related to Prime HDPE 250. Dish thickness shall be a uniform 1/8" thick or greater. Inflow dish shall have a minimum depth at the 90° vertical point of 3.8 inches and a minimum depth of five inches at the center point. Inflow dish body to be fabricated with molded ribbing members in bowl area for structural integrity. Inflow Dish to have smooth radius molded edges for additional strength and prevention of cracking. Inflow dish to have manufacture date (Month & Year) permanently molded in dish body for future warranty identification.

### Gasket Seal

The gasket seal shall be made of closed cell neoprene material and have a pressure sensitive adhesive on one side for adhering to inflow dish body, seating rim. Gasket to be 1/2" wide and shall have a minimum thickness of 1/8".

### Lift Strap

The Lift Strap shall be made from a woven polypropylene material, securely adhered to the inflow dish body interior, with a stainless steel assembly.

### Installation

For proper abatement results, the inflow dish, when installed, must seat fully flush within the manhole frame rim seat area. Frame must be cleaned of all dirt and debris prior to installation.

### Maintenance

USSSI recommends clients inspect inflow dish gasket seal on an annual basis. To ensure proper abatement performance, replacement of worn or missing gaskets may be required.

### Warranty

Five-year warranty on manhole inflow dishes standard. Manufacture date molded into Inflow Dish Body. Gasket Seal not included. Replacement gasket seals are available from USSSI.

### Manufacture

The Inflow Defender<sup>®</sup>, Manhole Inflow Dish, shall be furnished exclusively by Utility Sealing Systems Incorporated, Venice, Florida.

### Ordering Criteria

To ensure proper fit with manholes, inflow dishes are manufactured to specific measurements provided by the client. To order, please see USSSI Inflow Defender<sup>®</sup> Dish Technical Sheet.

### Engineering Approval

Inflow Dish manufacturer must provide specifying engineer with their inflow dish specifications and samples for review and acceptance.

### Additional Abatement Products & Technologies

For complete information on other Waste Water Infiltration & Inflow abatement products and technologies, please contact USSSI by phone or visit [www.ussiusa.com](http://www.ussiusa.com).