

1 - PRODUCT IDENTIFICATION

PRODUCT NAME: Leather Tech

PRODUCT TYPE: Neutral Liquid Vehicle Dressing

COMPANY: Top Line Chemical Solutions, LLC

1923 John Crosland Jr. Drive

Charlotte, NC 28208 1-980-309-0569

EMERGENCY PHONE:..... INFOTRAC: 1-352-323-5000 (International)

INFOTRAC: 1-800-535-5053 (North America)

2 - HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE: Eye Irritation (2A)

SYMBOLS:.....



SIGNAL WORD:..... WARNING!

HAZARD STATEMENT:..... Causes serious eye irritation

PRECAUTIONARY STATEMENTS:

PREVENTION: Wash hands thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

RESPONSE:..... IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do – continue

rinsing. If eye irritation persists get medical advice/attention.

STORAGE: N/A DISPOSAL: N/A

3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT

Water
Hydrotreated Light Distillates
Polydimethylsiloxane

C.A.S. NUMBER

7732-18-5 64742-47-8 63148-62-9

Percentages of ingredients are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals

4 - FIRST-AID MEASURES

BREATHING (INHALATION): ... If victim shows signs of discomfort or irritation, remove to fresh air. If symptoms persist, get immediate medical attention.

SWALLOWING (INGESTION): DO NOT INDUCE VOMITING! Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person.

Get immediate medical attention!

EYES:Flush eyes with a large quantity of fresh water for at least 15

minutes. If irritation persists, consult a physician.

SKIN (DERMAL): Flush from skin and clothing with large amounts of fresh water. If

irritation persists, consult physician. Wash contaminated clothing

before wearing.

5 - FIRE-FIGHTING MEASURES

FLASHPOINT:.....>180 degrees F.

EXTINGUISHING MEDIA:...... Water fog or fine spray. Carbon dioxide, Dry chemical or Alcohol

resistant foam.

SPECIAL FIRE FIGHTING PROCEDURES:Firefighters working in areas where this

product is present should be equipped with an approved, fully

enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS:......None known.

6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Dike to prevent spillage into streams or sewer systems. Consult

local, state and federal authorities.

WASTE DISPOSAL: As recommended by local, state and federal authorities.

7 - HANDLING and STORAGE

STORAGE: Store in a cool, well ventilated area. Avoid overheating or

freezing.

HANDLING:...... Do not place this product in an unmarked container! Keep away

from children! Spilled material is slippery. ATTENTION: Empty containers retain vapor and product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or

other sources of ignition. Do not reuse empty container.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not usually needed. Vapors not normally harmful.

PROTECTIVE CLOTHING:...... Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES: Do not place this product in an unmarked container! Keep away from children! Spilled material is slippery. ATTENTION: Empty

containers retain vapor and product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or

other sources of ignition. Do not reuse empty container.

INGREDIENT C.A.S. NUMBER PEL

Water 7732-18-5 No limits established Hydrotreated Light Distillates 64742-47-8 500 ppm PEL Polydimethylsiloxane 63148-62-9 No limits established

9 - PHYSICAL / CHEMICAL PROPERITES

APPEARANCE & ODOR: Slightly viscous white liquid, pleasantly scented.

ODOR THRESHOLD: N/A **pH**: 6.5-7.5

MELTING POINT: 210 degrees F.

FREEZING POINT: N/A

BOILING POINT:..... 210 degrees F.

BOILING POINT RANGE:..... N/A

FLASHPOINT:.....>180 degrees F.

EVAPORATION RATE:......N/A
FLAMMABILITY (solid/gas):.... N/A
EXPLOSION LIMITS:.....N/A
VAPOR PRESSURE:N/A

VAPOR DENSITY (AIR=1):...... Greater than 1.

SPECIFIC GRAVITY: 0.99

SOLUBILITY IN WATER: Dispersible.

PARTITION COEFFICIENT: N/A

AUTO-IGNITION TEMPERATURE:N/A
DECOMPOSITION TEMPERATURE:N/A

VISCOSITY: Significant body

10 - STABILITY and REACTIVITY

STABILITY: Stable under normal conditions.

HAZARDOUS DECOMP.:..... This product not known to polymerize.

INCOMPATIBILITY: Do not mix with other chemicals.

11 - TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:.....Inhalation, skin absorption, or ingestion.

LISTED CARCINOGEN: None over 0.1%.

MEDICAL CONDITION AGGRAVATED:.... May aggravate pre-existing dermatitis.

INHALATION:
*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6)
12 – ECOLOGICAL INFORMATION
ENVIRONMENTAL FATE AND DISTRIBUTION: N/A
13 -DISPOSAL CONSIDERATIONS
WASTE DISPOSAL: As recommended by local, state and federal authorities.
14 – TRANSPORTATION INFORMATION
PROPER SHIPPING NAME: Not D.O.T. regulated in these container sizes. HAZARD CLASS:
15 - REGULATIONS
Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200
16 – OTHER INFORMATION
NFPA HEALTH:
ADDITIONAL: The information contained in this SDS is based on the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury

from the use of this product. Be safe- read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it. This product and/or all of its components are either included on or exempt from the TSCA Inventory of Chemical Substances.

REVISION DATE:.... 09/24/19