## PRECON PRECAST, LLC 6868 FM 730 SOUTH AZLE, TX 76020

817-448-9718 OFFICE 817-448-9886 FAX frank@preconprecast.com

3500 SERIES
305.76 GALLON OIL RESERVE
FLEVATOR VALILT

General Notes: 1. Unit comes with interior piping installed. 2. Inflow section of unit must be filled with clear water prior to use.

**ELEVATOR VAULT** Specifications: 1. Concrete has design strength of 5,000psi @ 28 days. 2. Steel reinforcement: ASTM A-615, grade 60 ASTM A-497 welded wire fabric. 3. Designed for H2O loading. 4. CI Casting: ASTM A-48, class 30/35. 2" Vent 4" Outlet 4" Inlet 5'-2" Δ Δ Δ TOP VIEW 18" Dia. ADS Concrete **VISUAL** Riser (typ.) Lid PERFORATED HIGH STAINLESS w-3/16" OIL **ALARM** HOLES 2" Vent AUDIBLE Oil Reserve 305.76 gallons 4" Outlet 4" Inlet 6'-9" High Oil Level Float 4'-6" 575.12 gallons -5'-2"-SIDE VIEW

	APPROVED FOR PRODUCTION	AUTHORIZED BY
305galoilrsrvelevatorvault.dwg	DATE:	PRINT:
FILE NAME:	JOB TITLE:	SIGN: