# Personal Protective Equipment (PPE), Fall Protection, ACR / Flame Resistant Products



#### **PPE**

- · Eye Protection
- Head Protection
- Hearing Protection
- Respiratory Protection
- · Hand Protection
- Weather Protection
- Cut Protection
   Traffic Protection





#### **Fall Protection**

- Harnesses Belts
- · Positioning Belts
- Lanyards
- Ladder Straps
- Climbers
   Self Retracting Lifelines
- Tool Lanyards
- Rope Grabs
- Descenders
   Rope





### **SAFETY**

## Personal Protective Equipment (PPE), Flame Resistant, ARC





### Roll-Up STOP/SLOW Paddles



24" Diamond Grade™ Stop/Slow Paddle

#### **FEATURES:**

Complies with MUTCD standards	Sign rolls up and stores in bad with staff
Available in Non-Reflective, Super Bright and Diamond Grade reflective materials	Lightweight, easy deployment
Offered in 18" and 24" octagon	Comes with 3-piece plastic staff and heavy duty storage bag. Store size 3"x 8"x 38"

Easy to use

#### **MODELS**

#NRF183 - 18" Non-Reflective	# NRF243 – 24" Non-Reflective
# RF183 - 18" Suberbright	# RF243 - 24" Superbright
# RDG183 - 18" Diamond Grade	# RDG243 – 24" Diamond Grade

## School Signs









### **Construction Signs**



W4-2L Left Merge (symbol)



W9-1 Right Lane Ends



W20-1 Road Construction Ahead



W20-2 Detour Ahead



W20-3 Road Closed Ahead



W21-1a Workers (symbol)



M4-8 Detour



M4-10 Detour

### Warning Signs



W1-2R\*
Curve Right
\*W1-2L Curve Left also
available



W1-8 Chevron Alignment



W3-1 Stop Ahead



W3-3 Signal Ahead



W10-1 Railroad Crossing



W11-2 Pedestrian Advance



W11-3 Deer Crossing



W14-1 Dead End

# TWIN FLEX™ 60

-Model Number TF60



TF60 in display position with 48" x 48" rigid sign



TF60 base in display position



Heavy duty spring system flexes for stability in windy conditions.

### **FEATURES:**

- NCHRP-350 approved
- Compiles with MUTCD standards
- Displays 36" and 48" rigid and roll-up signs
- Features two vertical coil springs
- Aluminum and steel construction
- Quick set-up and tear down with kick release system for leg deployment
- Aluminum legs feature two position height adjustment and anti-kid foot pads
- Minimum height from ground to bottom of panel: 60"
- Closed storage dimensions: 12" x 10" x 92"
- Open footprint: 74" x 135"
- Weight: 48 lbs