

Fax:+86-576-87301690

ISO9001 🗐 🗲 (€















START FROM THE YEAR OF 1983

Since the company began from 1983, ZUPPER TOOL has experienced from "made in China" to "Created in China", We has become the leader of battery hydraulic tools in China more than 30 years

We build the tools for plumbing and heating installations last for years, but what we do can last forever. We manufacture best-in-class products by 300 strong highly trained team and sold over 100 countries.

We work continuously to improve the quality, efficiency and safety of our products to meet global market expectations and requirements. Accordingly many of our products are patented and comply with various international standards. ZUPPER products and you, together, WE BUILD.





set up provincial testing lab

MORE THAN 30 YEARS OF EXPERIENCE

IMPORTANT EVENTS OF ZUPPER TOOLS

From 1983 until now, ZUPPER TOOL has experienced from "made in China" to "Created in China", We has become the leader of battery hydraulic tools in China more than 30 years We build the tools for plumbing and heating installations last for years, but what we do can last forever.

1993

Yuhuan Hydraulic Tools Factory was established, which is the predecessor of ZUPPER TOOLS.

2003

JULI moved to a new factory, and entered the period of rapid development and regularization

of enterprise development.

1994

"Yugong" brand was recognized as "China market protection brand" by China Light Industry Product Quality Assurance Center

2008

JULI cooperated with Zhejiang University to develop battery hydraulic tools

2019 Scheme ERP program,

To be Recognized as High

2014

and new tech enterprises

2012

Draft the industry standard of "crimping tool for cables" and "manual cable cutter"

"ZUPPER" brand was born, and get Madrid certification

2011

2015


Implement 5S site management and production management

2020

Get the certificate of intellectual property rights













CERTIFIED FOR QUALITY AND THE ENVIRONMENT

ZUPPER for enhanced safety and optimized standards

For us, just meeting the standard is not enough, in terms of safety, efficiency and reliability. We are certified by ISO9001 certificate, CE by TUV, ETL etc. Environmental issues also play a crucial role. Our company is ISO 14001 certified. ZUPPER have 48 patents, including invention patents, patents for utility models and appearance patents.





TOP QUALITY FROM PRECISION PRODUCTION

To ensure the stability and high quality of our products, we purchase raw materials and components that guarantee first-class quality. We have more than 300 processing modern equipment; the latest CNC machines guarantee precision manufacturing for all tool components. The most important part is the key parts and processes of the product are completed in the factory to ensure that each product of the world class level.

TOP QUALITY FROM MULTIPLE DEPTH INSPECTION


We build provincial laboratory to test the raw material and important components, the only one in Zhejiang Province, it includes three coordinate measuring instruments, Keens 3D scanner,

Salt spray tester, profile meter, Image measuring instrument and spring testing and so on.

 $\mathbf{0}$


CONTENT

BATTERY POWERED PRESS TOOL 10-27 **ELECTRICAL POWERED** PRESS TOOL 28-31 **BATTERY POWERED AXIAL PRESS TOOL** 32-36 **EXPANDING TOOL** 37-42 & MANUAL PIPE TOOLS **BENDING TOOL PRESS JAWS**





SMALLER, FASTER, LIGHTER COMPACT MEASURES HUGE POWER



THE RIGHT TOOL FOR YOUR NEEDS

- CIRCUIT BOARD DIAGNOSTICS

 Alart you when the battery is low or the tool is too hot or cold
- OLED DISPLAY
- Easy reading on
- Battery Percentage
- Pressing Times
- Fault Code
- Maintenance Note

- 180° SWIVELLING BARREL
 - Easy access to connections
- TWO STAGE HYDRAULIC SYSTEM
 Hydraulic Ram Output provides more force for reliable connection
- ERGONOMIC DESIGN
 With light weight and inline grip, easily work overhead and in tight spaces.
- SERVICE INTERVAL: 30000 Cycles



CIRCUIT BOARD DIAGNOSTICS Alart you when the battery is low or the tool is too hot or cold







BATTERY POWERED PRESS TOOL

precise pressing with lighter body

- 15-28mm(1/2"-1")Stainless Pipe
- 15-35mm(1/2"-1 1/2")Copper Pipe
- 16-32mm PEX & Multi-layer Pipe

The PZ-1930 is the newest addition to the mini press tool with in-line grip, it is efficient and reliable way to join copper, stainless steel and PEX&Multi-layer Pipe.




















SPECIFICATIONS				
Capacity:	12-28mm(1/2-1") Stainless steel pipe,	Battery:	18V Li-ion 2.5A	\h
	12-35mm(1/2"-1") Copper pipe,	Battery Charger:	AC 100-240V	
	12-32mm PEX&Multi-layer pipe	Charging Time:	Approx. 50min	S
Output:	19KN	Service Interval:	Service Interva	al: 30000cycles
Stroke:	30mm	Weight:	Approx.2.0kgs	(tool with battery)
Oil capacity:	Approx. 60ml		Approx. 3.5kgs(tool with battery and jaw	
Crimping Cycle Time:	2-4S	Tool Size:	Tool Size: 363>	<120×75mm
Crimping Cycles/charge:	180cycles (DN 20 Stainless Steel)			
MODEL NO.	DESCRIPTION		Weight (KGS)	Standard Pack
PZ-1930	PZ-1930 Battery Press Tool K	it without jaws	6.10	1pc
	18V, 2.5 Ah Li-Ion Batteries		0.35	2pcs
	Charger		0.70	1pc
ACCESSORIES	ACCESSORIES Plastic case		2.90	1pc
	Sealing ring of cylinder:			1set
	Sealing ring of safety valve:			1set





SMALLER, FASTER, LIGHTER

EASY ONE-HAND USE, COMPACT, Powering Solutions for pressing technology



BZ-1930

BATTERY POWERED PRESS TOOL

improved ergonomic design and huge power in zupper hydraulic system

- Ergonomic designed with 30cm length and 2kgs lightweight, comfortable operation.
- The spare parts are made of high quality aviation aluminum
- Only 4~6S to finish one cycle press
- The tool includes two 18V, 2.0Ah Li-ion and one charger
- It is actuated by motor and controlled by MCU, with two stage hydraulic system.
- SERVICE INTERVAL 30000 cycles























SPECIFICATIONS					
Capacity:	12-28mm(1/2-1") Stainless steel pipe,	Battery:	18V Li-ion 2.5A	h	
	12-35mm(1/2"-1") Copper pipe,	Battery Charger:	AC 100-240V		
	12-32mm PEX&Multi-layer pipe	Charging Time:	Approx. 50mins	S	
Output:	19KN	Service Interval:	Service Interva	l: 30000cycles	
Stroke:	30mm	Weight:	Approx.2.4kgs	(tool with battery)	
Oil capacity:	Approx. 60ml		Approx. 3.9kgs(tool with battery and jaw)		
Crimping Cycle Time:	2.5-4S	Tool Size:	Tool Size: 300×286×75mm		
Crimping Cycles/charge:	180cycles (DN 20 Stainless Steel)				
MODEL NO.	DESCRIPTION		Weight (KGS)	Standard Pack	
BZ-1930	BZ-1930 Battery Press Tool Kit wi	thout jaws	6.50	1pc	
	18V, 2.5Ah Li-Ion Batteries		0.35	2pcs	
	Charger		0.70	1pc	
ACCESSORIES	Plastic case		2.90	1pc	
	Sealing ring of cylinder:			1set	
	Sealing ring of safety valve:			1set	





PZ-1550

BATTERY POWERED PRESS TOOL

Efficiency and Durability

- Battery press tool with in-line grip.
- SPEED UP 20% compare with old type. Only 3~4.5S to finish one cycle press
- The tool comes standard with two 18v,4.0Ah Lion-batteries and one charger. It can achieve over 350 cycles per charger.
- Motor drivers, Micro-computer control system, OLED screen and double valve hydraulic system.









STAINLESS STEEL PIPE



OLED Display

All tools can be controlled

by one trigger





PER CYCLE TIME

SPECIFIC	SPECIFICATIONS						
Capacity:	12-54mm(1/2"-2") for stainless steel pipe	Battery:	18V Li-ion 4.0Ah				
	12-108mm(1/2"-4") for PEX,Multi-layer and copper pipe	Battery Charger:	AC 100-240V				
Output:	32KN	Charging Time:	Approx. 80mins				
Stroke:	40mm	Service Interval:	30000cycles				
Cycle Time:	Approx. 3-4.5 seconds	Weight:	Approx.3.9kgs (tool with battery)				
Oil capacity:	115ml		Approx.6.1kgs(tool with battery and jaw)				
		Tool Size:	450×81×128mm				

PZ-1550 Battery Press Tool Kit					
MODEL NO.	DESCRIPTION	Weight(kgs)			
PZ-1550	PZ-1550 Battery Press Tool Kit without jaws	9.20			
FZ-1330	Battery, 18V, 4.0Ah Li-Ion	0.60			
ACCESSORRIES	Charger	0.70			
ACCESSURRIES	Plastic case	4.10			



POWERFUL, RELIABLE AND SIMPLY PRACTICAL

EFFICIENCY MAX SPEED UP 20%





OLED DISPLAY


MANUAL RETRACT IF NEED

ALL TOOLS CAN BE CONTROLLED BY ONE TRIGGER

THE RIGHT TOOL FOR YOUR NEEDS

HAMEN

- OLED Data Display to show crimping time, Electricity Quantity, maintenance reminding and fault code.
- Air Cooling Heat dissipation System to extend using life.
- Press head rotates 310°
- Two stage hydraulic system with fast feed and power control
- Quick motor stop guarantees highest safety for the operator
- Automatic retraction when crimp is completed
- Electronic control and monitor of crimping operation
- Ergonomic design and optimized position of centre of gravity



HIGH PERFORMANCE 18V Li-ion Battery



CIRCUIT BOARD DIAGNOSTICSAlart you when the battery is low or the tool is too hot or cold





ED-1550BATTERY POWERED PRESS TOOL FASTER & RELIABLE

 The ED-1550 is the newest addition to the press tool offered by ZUPPER, it gives another option for a fast and reliable way to join copper, stainless steel and PEX. The tool comes standard with two 18V, 4.0Ah Li-ion batteries and one charger, motor drives, Microcomputer control system, OLED screen and double valve hydraulic system, it can achieve over 300 cycles per charge.








MULTUL AVED COMPOSITE DI





STAINLESS STEEL PIPE







SPECIFIC	CATIONS				
Capacity:	12-54mm(1/2"-2") for	stainless steel pipe	Battery:	18V Li-i	on 4.0Ah
	12-108mm(1/2"-4") fo	r PEX,Multi-layer and copper pipe	Battery Charger:	AC 100	-240V
Output:	32KN		Charging Time:	Approx.	. 80mins
Stroke:	40mm		Service Interval:	30000cy	ycles
Cycle Time:	Approx. 3-8 seconds		Weight:	Approx.	.3.8kgs (tool with battery)
Oil capacity:	115ml	ml		Approx.	.6.0kgs(tool with battery and jaw)
			Tool Size:	388×32	2×84mm
ED-1550 E	Battery Press To	ol Kit			
MODEL NO.		DESCRIPTION			Weight(kgs)
ED 4550		ED-1550 Battery Press Tool Kit without jaws			9.15
ED-1550		Battery, 18V, 4.0Ah Li-lon		0.60	
		Charger			0.70
ACCESSORRIE	:5	Plastic case			4.10



ED-5050 BATTERY POWERED PRESS TOOL For thick stainless steel, copper

- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.

ED-60100


BATTERY POWERED PRESS TOOL

For big size from 60~108mm stainless steel pipe

- Designed with matching press jaws
 Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.



TECHNICAL DATA	ED EGEG	FD /0100
TECHNICAL DATA	ED-5050	ED-60100
Pressing range:	12-54mm(1/2"-2") for stainless steel pipe	60-108mm(2"-4") for stainless steel pipe and
	12-108mm(1/2"-4") for PEX,Multi-layer and copper pipe	copper pipe
Rated pressure:	50KN	80KN
Stroke:	50mm	80mm
Time/work:	3-6s(depend on the dia of pipe)	10-25s(depend on the dia of pipe)
Cycles/charger:	180cycles	50cycles
Voltage/capacity:	18V/4.0Ah	18V/5.0Ah
Charging time:	Approx.80mins	Approx.100mins
Charging voltage:	AC 100V ~ 240V ;50 ~ 60Hz	AC 100V ~ 240V ;50 ~ 60Hz
Package:	Plastic box	Plastic box
Ambient temperature:	-10 ~ 40°C	-10 ~ 40°C
Service Interval:	30,000cycles	15,000cycles
Weight:	4.7kgs(with battery)	11.9kgs(with battery)
ACCESSORIES		
Battery:	2pcs	2pcs
Charger:	1pc	1pc
Sealing ring of cylinder:	1set	1set
Sealing ring of safety valve:	1set	1set



NEW TECHNOLOGY OF EB SERIES BRUSHLESS MOTOR

No carbon brush, durability and reliability



BRUSHLESS MOTORS ARE DRIVING REVOLUTIONARY PERFORMANCE



Longer life and maintenance-free thanks

to brushless technology

LONGER **MOTOR LIFE**

MORE **POWER**

No carbon brush. When the motor is running there is no power loss by friction and reduce the heat generated by the motor.

MORE RUN-TIME

Heat generated by Brushless motor is small Compared to the brush motor, the brushless motor will do more work in the same full

charge of the battery pack

+30%



APPLICATION

No carbon brush, the motor does not produce sparks at work, it is more suitable used in combustible place



EB-1550 EB-32100 **BATTERY POWERED PRESS TOOL**

NEW TECHNOLOGYBRUSHLESS MOTOR

- 3-6S to finish one cycle
- Automatic retraction when press is completed
- Two stage hydraulic system
- An ergonomic design and optimized position of center of gravity to provide increased feel and usability
- Micro computer control system



BLUETOOTH AND PRESSURE SENSOR

Thanks to new implemented Bluetooth technology, devicerelated data can be requested via the ZUPPER APP. The ZUPPER EB Series include BLUETOOTH asbasic configuration,you can choose pressure sensor at optional.

ZUPPER Check-APP

- Data transfer between press tool and APP
- See the location of where your ZUPPER Link enabled tool was
- Check the pressure by pressure sensor to differentiate the pressure normal or not.
- APP shows the pressure data counter to check and analyze



TECHNICAL DATA	EB-1550		EB-32100
Capacity:	12-54mm(1/2"-2") for stainless steel pipe	Э	12-54mm(1/2"-2") for stainless steel pipe
	12-108mm(1/2"-4") for PEX,Multi-layer a	nd copper pipe	12-108mm(1/2"-4") for PEX,Multi-layer and copper pipe
Output:	32KN		32KN
Stroke:	40mm		40/60/100mm(adjustable)
Cycle time:	3~6s(depands on diameter of pipe)		3~6s(depands on diameter of pipe)
Oil capacity:	115ml		250ml
Pressing cycles/charge	360cycles(DN20 stainless steel)		360cycles(DN20 stainless steel)
Battery:	18V Li-ion 4.0Ah		18V Li-ion 4.0Ah
Charger:	AC 100V~240V 50~60Hz		AC 100V~240V 50~60Hz
Charging time:	Approx.80mins		Approx.80mins
Service Interval:	30000cycles		30000cycles
Weight:	3.8kgs(tool with battery)		
	6.0kgs(tool with battery and jaw)		
Tool Size:	395x318x86mm		525x318x86mm
ACCESSORIES			
	ED 1650	\\/-:- -+()	FD 22100

ACCESSORIES				
	EB-1550	Weight(kgs)	EB-32100	
	Battery Press Tool Kit without jaws:	9.15	Battery Press Tool Kit without jaws:	
Accessories:	18V Li-ion 4.0Ah	0.6	18V Li-ion 4.0Ah	
Accessories.	Charger	0.7	Charger	
	Plastic case	4.1	Plastic case	

Kit includes: EB-1550 battery press tool, Two 4.0Ah Batteries, One Charger and Carrying case





BZ-1550 BATTERY POWERED PRESS TOOL

220V Lasting Power Supply High performance, Save time

- Battery press tool with gun type grip.
 Jaws are made of high strength forging steel.
 LED light for low or no-light environment

- LCD data display can show pressing times, electricity quantity and maintenance reminding information
- The tool comes standard with two 18v,4.0Ah Lion-batteries and one charger. It can achieve over 300 cycles per charger.
- Motor drivers, Micro-computer control system, and double valve hydraulic system.











STAINLESS STEEL PIPE








SPECIFICATION	IS			
Capacity:	12-54mm(1/2	2"-2") for stainless steel pipe	Battery:	18V Li-ion 4.0Ah
	12-108mm(1	/2"-4") for PEX,Multi-layer and copper pipe	Charger:	AC 100V~240V 50~60Hz
Output:	32KN		Charging time:	Approx.80mins
Stroke:	40mm		Service Interval:	30000cycles
Cycle time:	3~6s(depand	s on diameter of pipe)	Weight:	4.5kgs(tool with battery)
Pressing cycles/charge	350cycles(DN	120 stainless steel)		6.7kgs(tool with battery and jaw)
			Tool Size:	375x329x85mm
Accessories:				
MODEL NO.		DESCRIPTION		Weight(kgs)
BZ-1550		BZ-1550 Battery Press Tool Kit without jaws 18V Li-ion 4.0Ah		9.85
DZ-1330				0.6
ACCECCODDIEC		Charger		0.7
ACCESSORRIES		Plastic case		4.1

Antislip handle







CZ-1550

ELECTRICAL POWERED PRESS TOOL

- Only 3S to finish one cycle press
- Press jaw with piston, to avoid maloperation
- Anti-slip handle and an optimized center of gravity
- Motor drives, Micro-computer control system and double valve hydraulic system.










STAINLESS STEEL PIPE





SPECIFICA	TIONS				
Capacity:	12-54mm(1/2"-2") for stainless steel pipe	Rated Power:	490V	1	
	12-108mm(1/2"-4") for PEX,Multi-layer and copper pip	e Voltage:	AC22	20V 50/60HZ (or AC 110V 50/60)HZ
Output:	32KN	Weight:	4.95	gs(without jaw)	
Stroke:	40mm	Size of tool:	450*	81*130mm	
Cycle time:	3S(DN25)	Hydraulic oil:	Shell	Tellus S2V HV15 130ml	
Accessories	:				
MODEL NO.	DESCRIPTION			Weight(kgs)	
CZ-1550	CZ-1550 Press Tool Kit v	vithout jaws		8.15	
CZ-133U					





HH-1550

ELECTRICAL POWERED PRESS TOOL

520W High power 220V lasting power supply, Reliable and Stable

- Only 3S to finish one cycle press
- Press jaw with piston, to avoid maloperation.
- Anti-slip handle and an optimized center of gravity for easier carry.
- Motor drives, Micro-computer control system and double valve hydraulic system.







MULTI-LAYER COMPOSITE PIPE





STAINLESS STEEL PIPE





SPECIFIC	SPECIFICATIONS						
Capacity:	12-54mm(1/2"-2") for stainless steel pipe	Rated Power:	520W				
	12-108mm(1/2"-4") for PEX,Multi-layer and copper pipe	Voltage:	AC220V 50/60HZ (or AC 110V 50/60HZ)				
Output:	32KN	Service Interval:	30000cycles				
Stroke:	40mm	Weight:	4kgs(without jaw)				
Cycle time:	2.6-6S	Size of tool:	414*328*82mm				
		Hydraulic oil:	Shell Tellus S2V HV15 130ml				

	HH-1550 Press Tool Kit					
	MODEL NO.	DESCRIPTION	Weight(kgs)			
LIII 1EEO	HH-1550	HH-1550 Press Tool Kit without jaws	7.2kgs			
	HH-1330	Plastic case	3.2kgs			





PZ-1240PE

BATTERY POWERED AXIAL PRESS & EXPAND TOOL

PZ-1240PE is the newest addition to the mini axial press & expand tool, it is efficient and reliable way to expand and connect PEX with fittings,

it is powered by Li-ion, actuated by motor and controlled by MCU. With two stage hydraulic system.

SPECIFICATIONS			
Output	18KN	Accessories:	
Stroke:	39mm	Battery:	2 pcs, 0.35 KGS/PC
Connecting range:	PEX pipe:16-32mm	Charger:	1 pc 0.70 KGS
	Multi-Layer pipe16-25mm	Carrying case	1pc 4.10 KGS
Expanding/Connecting range:	16x2.2, 20x2.8, 25x3.5, 32x4.4mm	Sealing ring of cylinder:	1 set
Voltage of battery:	DC 18V,2.5Ah	Sealing ring of safety valve:	1 set
Connecting cycle time	Approx. 2.5-5S		
Charging voltage:	AC 100V~240V ;50~60Hz		
Charging time:	Approx.50mins		
Size of tool:	405x242x92mm		

THE RIGHT TOOL FOR YOUR NEEDS

CIRCUIT BOARD DIAGNOSTICS

Alart you when the battery is low or the tool is too hot or cold

OLED DISPLAY

- Easy reading on
- Battery Percentage
- Pressing Times
- Fault Code
- Maintenance Note

360° SWIVELLING BARREL Easy access to connections

TWO STAGE HYDRAULIC Hydraulic Ram Output provides more force for reliable connection

ERGONOMIC DESIGN

With light weight and inline grip, easily work overhead and in tight spaces.

SERVICE INTERVAL: 30000 Cycles



Kit includes: PZ-1240PE AXIAL PRESS&EXPAND TOOL, Two pairs of connecting jaws, Three expanding dies, One cutter, Two 2.5Ah Batteries, One Charger and Carrying Case.



PZ-1240PE

BATTERY POWERED AXIAL

PRESS & EXPAND TOOL









PZ-1240

BATTERY POWERED AXIAL PRESS TOOL

PZ-1240 is the newest addition to the mini axial press tool, it is efficient and reliable way to connect PEX with fittings, it is powered by Li-ion, actuated by motor and controlled by MCU. With two stage hydraulic system.

SPECIFICATIONS				
Output:	18KN	Accessories:		
Connecting range:	PEX pipe:16-32mm	Battery:	2 pcs, 0.3	5 KGS/PC
	Multi-Layer pipe16-25mm	Charger:	1 pc 0.7	0 KGS
Connecting range:	16x2.2, 20x2.8, 25x3.5, 32x4.4mm	Carrying case	1pc 4.1	KGS
Connecting stroke:	39mm	Sealing ring of cylinder:	1 set	
Voltage of battery:	DC 18V,2.5Ah	Sealing ring of safety valve:	1 set	
Connecting cycle time	Approx. 2.5-5S			
Charging voltage:	AC 100V~240V ;50~60Hz			
Charging time:	Approx.50mins			
Size of tool:	408x216x75mm			

THE RIGHT TOOL FOR YOUR NEEDS

CIRCUIT BOARD DIAGNOSTICS

Alart you when the battery is low or the tool is too hot or cold

OLED DISPLAY

- Easy reading on
- Battery Percentage
- Pressing Times
- Fault Code Maintenance Note

360° SWIVELLING BARREL

Easy access to connections

TWO STAGE HYDRAULIC

Hydraulic Ram Output provides more force for reliable connection

ERGONOMIC DESIGN

With light weight and in-line grip, easily work overhead and in tight spaces.

SERVICE INTERVAL: 30000 Cycles







SMALLER, FASTER, LIGHTER
RELIABLE PRECISION FOR SUSTAINED USE **PZ-4523 BATTERY POWERED AXIAL PRESS TOOL**







PZ-4523

BATTERY POWERED PRESS TOOL

BATTERY POWERED AXIAL PRESS TOOL


PZ-4523 is the newest addition to the axial press tool for air conditioning pipe connecting.
It is powered by Li-ion, actuated by motor and controlled by MCU. With double valve hydraulic system, it is a perfect tool to be used in air conditioning systems, heating systems, refrigeration systems and water supply systems.

22.2,
1

• The dies for the tool is optional, there are split type and integral type:

• Split type: 6.35, 9.52, 12.7, 15.88, 19.05, 22.2, 25.4mm

• Integral type: 28.6, 31.8, 34.9, 38.1mm





Kit includes: PZ-4523 AXIAL PRESS TOOL, Two pairs of connecting jaws, Two 2.5Ah Batteries, One Charger and Carrying Case.



HAND-OPERATED HYDRAULIC PRESS TOOLS

Compact, Lightweight, Innovative

ZUPPER hand-operated hydraulic press tools performed as most convenient and high forces by hand. The tools offer you comfortable experience with the ergonomic design and lightweight aluminum housing.

HZ-1632 HAND-OPERATED HYDRAULIC PRESS TOOL

- With interchangeable dies
- 350° rotating head
- Two stage hydraulic system with fast feed and power stroke
- Light weight due to high quality aluminum housing
- Automatic retraction when crimping is completed

 With safety valve to prevent pressure overload. 		
Technical data		
Press range:	Ф16-32mm	
Rated press force:	60KN	
Rated work pressure:	63Мра	
Stroke:	17mm	
Length:	460mm	
Weight:	3.3kgs	
Package:	Metal box	











Multi-layer composite pipe FHT-1550

HYDRAULIC PRESS HEAD

- Forged jaws with high strength, sturdy and durable
- Hand pump,foot pump and electrical pump optional

Technical data	
Press range:	12-54mm(1/2"-2") for stainless steel pipe
12-108r	mm(1/2"-4") for PEX,Multi-layer and copper pipe
Rated press force:	32KN
Rated work pressure:	33Mpa
Stroke:	40mm
Package:	Metal box

HZ-1550 HAND-OPERATED HYDRAULIC PRESS TOOL

Forged jaws with high strength, sturdy and durable 350° rotating head Two stage hydraulic system with fast feed and power stroke Light weight due to high quality aluminum housing Automatic retraction when crimping is completed With safety valve to prevent pressure overload.

Technical data

i cerimicat aata		
Press range:	12-54mm(1/2"-2") for stainless s	teel pip
	12-108mm(1/2"-4") for PEX,Multi-layer and cop	per pip
Rated press force:		32KI
Rated work pressur	e:	33Mp
Stroke:		40mn
Package:	N	Metal bo

36







HYDRAULIC AXIAL PRESS TOOL

- Interchangeable connecting jaws, suit for different pipes
- 360° rotating head, suit for narrow space

Technical data	
Rated press force:	18KN
Rated work pressure:	45Mpa
Connecting range:	PEX pipe:16-32mm
	Multi-layer pipe:16-25mm
Weight:	4.5kgs
Stroke:	40mm
Package:	Metal box
Accessorries:	
Connecting jaws:	φ16x2.2-20x2.8,25x3.5-32x4.4mm





HEP-1213

HYDRAULIC EXPAND TOOL

- Aluminum alloy forged tool body,light and handy
- Interchangeable expanding dies, suit for copper pipe, aluminum pipe and stainless pipe
- Ergonomic design for one handed operation

Technical data	
Rated pressure:	12KN
Stroke:	13mm
Expanding range:	3/8"-1 1/8"
Expanding dies:	3/8",1/2",5/8",3/4",7/8",1",1 1/8"
Suit for:	copper pipe, aluminum pipe and stainless pipe
Weight:	0.95kgs(with 3/4" die)
Size of tool:	221x134x46mm



FT-1240

MANUAL AXIAL PRESS TOOL

- Sliding connections for PEX and Multi-layer composite pipe
- Connecting jaws made of alloy steel with precision casting, ratchet drive makes durable and reliable
 Connecting jaws built-in anti-attrition bushing makes easy sliding
 Expander handle made of high-strength aluminum alloy with
- precision forging, light and handy

Technical data		
Connecting/Expan	ding range:	PEX pipe:φ16-32mm
	Mult	i-layer pipe:φ16-25mm
Cutting range:		Max φ40mm
Weight:		5.2kgs
Stroke:		40mm
Package:		Plastic box
Accessorries		
Connecting jaws:	φ16x2.2-20	0x2.8,25x3.5-32x4.4mm

Kit includes:

One axial press tool and expand tool, cutter Two pairs connecting jaws, three expanding jaws and carrying case



ETM-20/ETM-32 MANUAL EXPAND TOOL

· Made of steel with precision casting

Technical data	
ETM-20 Expanding range:	Ф16-20mm
ETM-20 Length:	160mm
ETM-20 Weight:	0.33kgs
ETM-32 Expanding range:	Ф16-32mm
ETM-32 Length:	180mm
ETM-32 Weight:	0.58kgs



FT-1225 MANUAL AXIAL PRESS TOOL

- Easy changeable sliding jaws
- Smart tool body,easy one handed operation



MANUAL TOOL

FT-1218 MANUAL AXIAL PRESS TOOL

- Easy changeable sliding jaws
- Smart tool body,easy one handed operation

Technical data	
Connecting range:	φ12-25mm
Expanding range:	φ16-25mm
Cutting range:	Max φ42mm
Stroke:	80mm
Package:	Plastic box
Accessorries	
Jaws:	φ12,16,20mm

PATENT NO.:ZL 2004 3 0035588.1





TE-1632 MANUAL EXPAND TOOL

 Expander handle made of high-strength aluminum alloy with precision forging, light and handy.

LE-1 635	MANUAL EXPAND TOOL

 Expander handle made of high-strength aluminum alloy with precision forging, light and handy.

ETM-20 Expanding range: Ф16-20mm ETM-20 Length: 160mm ETM-20 Weight: 0.33kgs ETM-32 Expanding range: Ф16-32mm ETM-32 Length: 180mm ETM-32 Weight: 0.58kgs	Technical data	
ETM-20 Weight: 0.33kgs ETM-32 Expanding range: Φ16-32mm ETM-32 Length: 180mm	ETM-20 Expanding range:	Ф16-20mm
ETM-32 Expanding range: Φ16-32mm ETM-32 Length: 180mm	ETM-20 Length:	160mm
ETM-32 Length: 180mm	ETM-20 Weight:	0.33kgs
En 1 52 Length.	ETM-32 Expanding range:	Ф16-32mm
ETM-32 Weight: 0.58kgs	ETM-32 Length:	180mm
	ETM-32 Weight:	0.58kgs

Technical data	
Expanding range:	Ф16-32mm
Expanding dies:	Ф16-20,25,32mm
Length:	395mm
Weight:	1.33kgs

Technical data	
Expanding range:	Ф16-32mm
Expanding dies:	Ф16,20,25,32mm
Length:	395mm
Weight:	2.12kgs















JT-1632 MANUAL PRESS TOOL

360° rotating head

MANUAL TOOL

- Fast Change of crimping die without readjustment by special fixing system
- With telescope handles, effort-saving

Technical data	
Press force:	40KN
Stroke:	16mm
Package:	Plastic box
Accessorries	
Press die for V type:	φ12,15,18,22,28mm
Press die for U type:	φ16,20,25,32mm
Press die for TH type:	φ16,20,26,32mm

Note:The accessories type used at optional



- Quick-change mounting for simple dies changing
- Lever-type handle for easy press
- Ratchet locking type,ensure accurate reliability press

Technical data	
Weight:	3.0kgs
Length:	566mm
Package:	Plastic box
Accessorries	
Press die for U type:	φ16,20,25,32mm
Press die for TH type:	φ16,20,26,32mm

Note:The accessories type used at optional

JT-1626	MANUAL PRESS TOOL
---------	-------------------

- Ratchet locking type,ensure accurate reliability press
- Quick-change mounting for simple dies changing
 Antiskid handle structure designed make the press process more comforable

Technical data	
Weight:	2.1kgs
Length:	467mm
Package:	Plastic box
Accessorries:	
Press die for U type:	φ16,20,25mm
Press die for TH type:	φ16,20,26mm

Note:The accessories type used at optional

PEX PIPE PRESS TOOL FT-1824

- Stamping handle with heat treatment.Intensify,durable and reliable
- Comfortable skid resistance cover
- Alloy steel forged clamp arm is processed by CNC and strengthen by heat treatment, sturdy and durable

Technical data	
Press range:	φ18(1/2'')-φ24(3/4'')
Length:	290mm
Weight:	0.95kgs
Package:	Paper box

FT-1824B PEX PIPE PRESS TOOL

- Stamping handle with heat treatment.Intensify,durable and reliable
- Comfortable skid resistance cover
- Alloy steel forged clamp arm is processed by CNC and strengthen by heat treatment, sturdy and durable

Technical data	
Press range:	φ18(1/2'')-φ24(3/4'')
Length:	400mm
Weight:	1.60kgs
Package:	Paper box

FT-1530 PEX PIPE PRESS TOOL

- Mechanical crimping tool for connecting fitting with pipe Crimp XPAP, PEX with fittings up to φ30mm
- Technical data φ15mm(3/8")-30mm(1") Press range: Press dies· φ 15mm(3/8"),18(1/2"),20(5/8"),

FIESS ules:	+ 1011111(0/0),10(1/2),20(0/0),
	24(3/4"),30mm(1")
Length:	330mm
Weight:	1.6kgs
Package:	Plastic box



JT-1620	MANUAL PRESS TOOL
Technical data	
Weight:	1.7kgs
Length:	467mm
Package:	Plastic box
Accessorries:	
Press die for U	type: φ16,20mm
Press die for Th	l type: φ16,20mm

Note:The accessories type used at optional



FT-15B/18	3B/24B	PEX PIPE PI	RESS TOOL
Technical da	ta		
Model	FT-15B	FT-18B	FT-24B
Press range:	φ15(3/8")	φ18(1/2")	φ24(3/4")
Length:	310mm	310mm	310mm
Weight:	1.30kgs	1.30kgs	1.30kgs
Package:	Paper box	Paper box	Paper box



ZT-1824	PEX PIPE PRESS TOOL
Technical data	
Press range:	φ18(1/2'')-φ24(3/4'')
Length:	400mm
Weight:	1.20kgs
Package:	Paper box



FT-15/18/24		PEX PIPE PRESS TOOL		
Technical dat	а			
Model	FT-15	FT-18	FT-24	
Press range:	φ15(3/8")	φ18(1/2")	φ24(3/4	
ength:	275mm	275mm	300mm	
Weight:	0.9kgs	0.9kgs	1.0kgs	
Package:	Paper box	Paper box	Paper bo	



ZT-15/18/24		PEX PIPE PRESS TOOL	
Technical da	ta		
Model	Z T-15	ZT-18	ZT-24
Press range:	φ15(3/8")	φ18(1/2")	φ24(3/4")
Length:	330mm	330mm	370mm
Weight:	1.0kgs	1.0kgs	1.0kgs
Package:	Paper box	Paper box	Paper box



5/32 PVC PIPE CUTTI	
U-25	U-32
φ25mm	φ32mm
200mm	210mm
0.14kgs	0.15kgs
	U-25 φ25mm 200mm













U-42	PVC PIPE CUTTER
Technical data	
Max cutting range:	φ42mm
Length:	195mm
Weight:	0.26kgs

SSC-1530	PEX PIPE CINCH TOOL
Technical data	
Cinching range:	3/8",1/2",5/8,",3/4",1"
Weight:	0.6kgs
Length:	27.8mm
Package:	Blister card

0L	ST-1530 PEX CRIMI	ST-1530 PEX CRIMP RING REMOVAL TOOL		
	Technical data			
/4",1"	Removal range:	Max up to 1"		
0.6kgs	Weight:	0.3kgs		
.8mm	Length:	22mm		
r card	Package:	Blister card		



PS-1632A	DEBURRING TOOL
Technical data	
Features:	For multilayer composite and Pex pipe up to φ32mm
Deburring range:	φ16,20, 26,32mm





- Cutting device made of steel for long lifetime and with sharp cutting edge
 Large opening for removing pipe chips
 Anodic oxidation aluminium alloy sleeve is light and wear-resisting
 Hexagonal connector for changing different sizes easily,for handle,standard bit connectors or cordless screw driver







Technical data	
Features:	For multilayer composite and Pex pipe up to φ32mm
Deburring range:	φ16,20, 26,32mm



TB-22

Ideal in confined spaces

Bending formers easily changedOptimal bending results

• Quick release and resetting of bending formers





HYDRAULIC BENDING TOOL

TBJ-32 MANUAL BENDING TOOL

- For accurate one handed bending up to 90°, suit for copper and XPAP, PEX pipe
- Ideal in confined spaces
- Quick release and resetting of bending formers
- Bending formers easily changed
- Optimal bending results

Technical data			
Former in inch		Former in metric	
Size	Weight	Size	Weight
1/4 "	OD8kg	10mm	020kg
5/16 "	0D9kg	12mm	024kg
3/8 "	0D9kg	14mm	030kg
1/2 "	0.13kg	15mm	030kg
5/8 "	0.145kg	16mm	030kg
3/4 "	0.19kg	18mm	038kg
7/ 8"	021kg	20mm	041kg
		22mm	0 42kg

• For accurate one handed bending up to 90°, suit for 10-22mm(1/4"-7/8") thickness below 1.5mm copper pipe

Technical dat	ta		
Former in met	ric		
Size	Weight	Copper pipe	XPAP,PEX pipe
16mm	0.14kg	√	√
20mm	0.18kg	V	√
26mm	024kg	×	√
32mm	042kg	×	√



TBJ-22 MANUAL BENDING TOOL

- $^{\bullet}~$ For accurate one handed bending up to 90°, suit for 10-22mm(1/4"-7/8") thickness below 1.5mm copper pipe
- Ideal in confined spaces
- Quick release and resetting of bending formers
- Bending formers easily changed
- Optimal bending results

Technical da	ita		
Former in inch		Former in met	ric
Size	Weight	Size	Weight
1/4 "	008kg	10mm	020kg
5/16 "	009kg	12mm	024kg
3/8 "	009kg	14mm	030kg
1/2 "	0.13kg	15mm	030kg
5/8 "	0.145kg	16mm	030kg
3/4 "	0.19kg	18mm	038kg
7/8"	021kg	20mm	041kg
		22mm	0 42kg

42

BENDING TOOL



PRESS JAWS



Advantage of Zupper press jaw

Serial NO. • Tracking numbers easier to do Connecting Plate after-sales service Precision stamping Security design

Precision Forged Jaws

- Made by multi-axis CNC machine
- High strength, sturdy and durable

Special heat treatment process

• Inspection control program to ensure long span life

ZUPPER TOOL have a wealth of design and practical experience, can provide customers with differentiated solutions according to customer needs, and to offer customers with pipe press technical support.

Suitable press tool

- Compact series press jaws, suit for output 19KN press tool: PZ-1930,BZ-1930,EZ-1930 and so on
- Standard series press jaws, suit for output 32KN press tool: PZ-1550,CZ-1550,EB-1550,ED-1550,BZ-1550,HH-1550,HZ-1550,FHT-1550 and so on
- Thicken series press jaws, suit for output 50KN press tool: ED-5050,HH-5050 and so on







Compact series press jaws

Standard series press jaws

Thicken series press jaws







Universal Jaw with interchangeable dies fit for PEX pipe

Adaptor / Press Rings for 42-54mm

Economic design for any need

Interchangeable dies

- 1) One universal jaw with different types of dies, with a high cost performance
- 2) Quick change mounting for replace the dies easily

NOTE:The economic design only for PEX or PAP pipe, not for stainless pipe and copper pipes.



PRESS JAWS



	ss Jaws & Press		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	TH16	2.05	1
DEVO MULTILI AVED DIDE	TH20 TH25	2.00	
PEX& MULTI-LAYER PIPE	TH26	2.05	
	TH32	2.10	
	TH40	-	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	U16	1.95	
	U20	2.05	
	U25	2.00	
PEX& MULTI-LAYER PIPE	U32	2.15	
	U40	2.20	
	U50	-	
	U63	2.47	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	SV13	2.01	
FOR STAINLESS STEEL	SV20	2.07	- Drill
PIPE	SV25	2.03	
	SV30	-	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VAU15	2.00	
	VAU20	2.06	
	VAU25	2.04	13
FOR COPPER PIPE	VAU32	2.09	
	VAU40	1.48	
	VAU50	1.75	

Standard Series Pre	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VUS1/2"	2.00	
	VUS3/4"	2.10	
FOR COPPER PIPE	VUS1"	2.05	
FUR CUPPER PIPE	VUS1-1/4"	2.08	
	VUS1-1/2"	4.30	
	VUS2"	4.18	

	DESCRIPTION	JAW SIZE	Weight (KGS)	
		M12	2.00	
		M15	2.00	100
		M18	1.95	
		M22	2.00	
		M28	2.00	
F	FOR STAINLESS STEEL	M35	2.05	
	COPPER PIPE	M42	1.35	
		M54	1.60	

DESCRIPTION	JAW SIZE	Weight (KGS)	
	V12	2.02	
	V15	1.95	
	V18	2.10	
	V22	2.05	
	V28	2.00	
FOR STAINLESS STEEL	V35	2.05	
/COPPER PIPE	V42	1.40	
	V54	1.63	






Compact Series Pre	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	TH16	1.27	
	TH20	1.33	
PEX& MULTI-LAYER PIPE	TH25	1.41	
	TH26	1.35	
	TH32	1.40	
DESCRIPTION	JAW SIZE	Weight (KGS)	
DEVO MILITI I AVED DIDE	U16	1.20	
PEX& MULTI-LAYER PIPE	U20	1.29	
	U25	1.30	
	U32	1.50	

DESCRIPTION	JAW SIZE	Weight (KGS)
	M12	1.23
FOR CTAINILECC CTEEL	M15	1.30
FOR STAINLESS STEEL /COPPER PIPE	M18	1.29
/CUPPER PIPE	M22	1.37
	M28	1.39



DESCRIPTION	JAW SIZE	Weight (KGS)
FOR STAINLESS STEEL /COPPER PIPE	V12	1.23
	V15	1.23
	V18	1.29
	V22	1.38
	V28	1.47
	V18 V22	1.29 1.38



DESCRIPTION	JAW SIZE	Weight (KGS)
	SV13	1.23
FOR STAINLESS STEEL	SV20	1.27
PIPE	SV25	1.34
	SV30	-



Compact Series Pr	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VAU15	1.23	
FOR COPPER PIPE	VAU20	1.28	
	VAU25	1.35	
	VAU32	1.49	

DESCRIPTION	JAW SIZE	Weight (KGS)
	VUS1/2"	1.23
FOR COPPER PIPE	VUS3/4"	1.26
	VUS1"	1.48



PRESS JAWS