

AZTEC

INDUSTRIES

PRODUCT SPECIFICATIONS

WIRE TACK PANELS

AZTEC WireTack Panels are available in a variety of sizes. A square edge treatment is standard. Chamfered edge details are also available. All panels are fabric wrapped on face and edges, returning onto the back surface. Multiple 2" wide vertical splines, one on each side edge and additional center splines, based on width of panel, allow for wire passage behind the panel. A wide variety of fabrics are available. COM, with our approval. Installation is with factory mounted hook & loop fasteners.

SPECIFICATIONS

Inner Construction

Mineral Board with a 22-28 PCF density range.

Facing Materials

Our standard is a 100% polyester fabric, with a class A fire rating. Many optional fabrics, also class A rated, are available. COM with our approval.

Sizes

Available to 5' x 10'. Longer lengths limited only by handling restrictions. Panel thickness – 1" (1/2" surface panel with 1/2" splines) Panel appears 1" thick from side.

Acoustical Rating

NRC of .35 per ASTM E84
STC Rating of 25 (1/2" panel)

Fire Rating

Class A per ASTM E-84

TYPICAL APPLICATIONS

- Offices
- Computer Rooms
- Educational and Training Facilities
- Hospitals and Clinics
- Libraries
- Home Theatres