

35BL

POWDER FREE BLUE NITRILE

35BL Disposable Nitrile Examination Gloves offers healthcare professionals a performing glove that provides reliable barrier protection and tactility they require. The contrasting blue color stands out visibly than other blue nitrile gloves in the marketplace. This glove is also certified as Category III PPE and offers protection against chemicals and virus.

KEY FEATURES

*Medical Device Class I / CLASS A (Low Risk)
PPE Category III – Chemical Protective & Virus
Protective*

*High contrast blue, ideal for food handling
Accelerator Free Formulation*



DISPOSABLE **BLUE** NITRILE EXAMINATION GLOVES

EXCELLENT BARRIER PROTECTION
CHEMICAL PROTECTIVE
PUNCTURE RESISTANT
GREAT ELASTICITY
EXCELLENT GRIP
EASY DONNING
NON STERILE
LATEX FREE
SINGLE USE

AVAILABLE SIZES

XS 5-6	S 6-7	M 7-8	L 8-9	XL 9-10
--------	-------	-------	-------	---------



Recommended For

- **Healthcare Professionals**
- **Veterinary Use**
- **Skilled Nursing Centers**
- **First Responders**
- **Chemical Handling in Laboratory Use**
- **Pharmacies / Medical Compounding**
- **Food and Beverages Industry**

"Great replacement for Latex"



EN 374-5



MDA Registration Number: GA1509421-79520

EU Type Examination carried out by CENTEXBEL, Belgium (CE 0493)

Module D Conformity Assessment carried out by SGS Fimko OY, Finland (CE 0598)

PRODUCT DESCRIPTION

3.5g, Blue Disposable Powder Free Nitrile Glove, 240mm
Examination Gloves / PPE Cat. III / Food Handling
Accelerator Free Formulation
Finger Tip Textured
Beaded Cuff
Single Use
Non Sterile

MATERIAL

Acrylonitrile Butadiene Copolymer Latex

COLOR

Blue

PACKAGING

100 pieces of gloves in a dispenser box OR bags
10 dispensers / bags in a shipping case

STORAGE CONDITION

Recommended to store in a cool and dry place with
temperature below 30°C

SHELF LIFE

3 years

DIMENSION AND SPECIFICATIONS

Item	XS	S	M	L	XL	Inspection Level
Hand Size	6	7	8	9	10	(AQL)
Width	75±5mm	85±5mm	95±5mm	105±5mm	115±5mm	S2
Glove Length	240mm minimum	240mm minimum	240mm minimum	240mm minimum	240mm Minimum	AQL 4.0
Cuff Thickness	0.05mm ±0.02mm	0.05mm ±0.02mm	0.05mm ±0.02mm	0.05mm ±0.02mm	0.05mm ±0.02mm	S2 AQL 4.0
Palm Thickness	0.07mm ±0.02mm	0.07mm ±0.02mm	0.07mm ±0.02mm	0.07mm ±0.02mm	0.07mm ±0.02mm	
Finger Thickness	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	
Weight (Reference)	2.9g ±0.2g	3.2g ±0.2g	3.5g ±0.2g	3.9g ±0.2g	4.2g ±0.2g	

PERFORMANCE EVALUATION

Chemicals	ISO 374-1 / Type B Permeation Resistance	Breakthrough Time in (min)	EN 374-4 Degradation in (%)
J: Heptane	Level 6	>480	47.7
K: Sodium Hydroxide 40%	Level 6	>480	-25.6
T: Formaldehyde 37%	Level 6	>480	2.1

PHYSICAL PROPERTIES

	Standard	Before Ageing	After Ageing
Force at Break (N)	EN 455-2	min. 6N	min. 6N
Tensile Strength (Mpa)	ASTM D6319	min. 14	min. 14
Elongation (%)	ASTM D6319	500	400

OTHER PARAMETERS

Criteria	Inspection Level / AQL	Standard
Pinholes	G1 / AQL 1.5	
Major Visual	G1 / AQL 2.5	
Powder Content	max. 2mg/glove	ASTM D6124
Protein Content	N/A	ASTM D5712



ORDERING INFORMATION

Size	XS (5.5-6)	S (6.5-7)	M (7.5-8)	L(8.5-9)	XL(9.5-10)
Code	35BL – XS	35BL – S	35BL – M	35BL – L	35BL – XL

HARMONIZED STANDARDS

ASTM D6319, ASTM D6124, EN455 1-4, EN420:2003 + A1:2009, EN 1186, EN 374 1-5, EN 16523-1

ISO 10993- 1:2018;5:2009; 10:2013, ISO 15223-1:2016, ISO 1041:2008 + A1:2013, ISO 16604:2004,

ISO 3071:2020, ISO 13485:2016, ISO 9001:2015, FDA 21 CFR 177.2600



Contact us for ordering or more information



KGM GLOVES SDN. BHD.
LOT 18893 & 18894,
Jalan Perusahaan 9,
Kawasan Perusahaan Kamunting,
34600 Kamunting, Perak,
Malaysia.
Tel: +605-891 3612
Website: www.kgmgloves.com
Email: contact@kunng.com.my

