

50LP

NATURAL RUBBER LATEX

POWDER FREE

50LP is a versatile glove capable of multiple applications. This glove is specifically made to target the wider population offering barrier protection in whatever the end user is dealing with. This glove comes in handy for

FOOD HANDLING•DOMESTIC USE•GENERAL PURPOSE•INDUSTRIAL GRADE

KEY FEATURES

COMFORT FIT

Flexible and resilient
Rolled cuff is easy to wear and remove, prevents tearing during donning of glove

FOOD HANDLING

Passed US FDA 21 CFR 177.2600 tests
Powder free, ideal for food preparation and handling

COMPLIANCE

Manufactured in ISO 9001 & ISO 13485 certified facility meeting ASTM and EN harmonized standards



50LP Latex Powder Free Disposable Gloves is designed to provide

**DEPENDABLE BARRIER PROTECTION
EASY DONNING & COMFORT FIT
GREAT TACTILE SENSITIVITY
RESILIENT TO STRETCHING
EXCELLENT FLEXIBILITY
POWDER FREE•NON STERILE
GREAT GRIP•SINGLE USE**

Recommended for

FOOD PREPARATION•CAR WASHING•HOUSEHOLD USE•PAINTING•HAIR COLOURING•JANITORIAL WORK & MANY MORE



PRODUCT DESCRIPTION

5.0g, Powder Free Latex Gloves, 240mm
Palm Textured
Beaded Cuff
Single Use
Non Sterile

MATERIAL

Natural Rubber Latex

COLOR

Natural Latex Color / Tinge of Yellow

PACKING INFORMATION

100 pieces of gloves in a dispenser box OR
bags

10 dispensers / bags in a shipping case

STORAGE CONDITION

Recommended to store in a cool and dry place
with temperature below 30°C

SHELF LIFE

5 years

DIMENSION AND SPECIFICATIONS

Item	XS	S	M	L	XL	Inspection Level
Hand Size	6	7	8	9	10	(AQL)
Width	75±5mm	85±5mm	95±5mm	105±5mm	115±5mm	S2 AQL 4.0
Glove Length	240mm minimum	240mm minimum	240mm minimum	240mm minimum	240mm minimum	
Cuff Thickness	0.07mm ±0.02mm	0.07mm ±0.02mm	0.07mm ±0.02mm	0.07mm ±0.02mm	0.07mm ±0.02mm	
Palm Thickness	0.08mm ±0.02mm	0.08mm ±0.02mm	0.08mm ±0.02mm	0.08mm ±0.02mm	0.08mm ±0.02mm	S2 AQL 4.0
Finger Thickness	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	
Weight (Reference)	3.5g ±0.2g	4.5g ±0.2g	5.0g ±0.2g	5.5g ±0.2g	6.0g ±0.2g	

PHYSICAL PROPERTIES

	Standard	Before Ageing	After Ageing
Force at Break (N)	EN 455-2	min. 6N	min. 6N
Tensile Strength (Mpa)	ASTM D3578	min.18	min.14
Elongation (%)	ASTM D3578	min. 650	min. 500

OTHER PARAMETERS

Criteria	Inspection Level / AQL	Standard
Pinholes	G1 / AQL 1.5	
Major Visual	G1 / AQL 2.5	
Powder Content	max. 2mg/glove	ASTM D6124
Protein Content	max. 50ug/dm ²	ASTM D5712



Contact us for ordering or more information



KGM GLOVES SDN. BHD.
LOT 18893 & 18894,
Jalan Perusahaan 9,
Kawasan Perusahaan Kamunting,
34600 Kamunting, Perak,
Malaysia.
Tel: +605-891 3612
Website: www.kgmgloves.com
Email: contact@kunng.com.my

ORDERING INFORMATION

Size	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)
Code	50LP - XS	50LP - S	50LP - M	50LP - L	50LP - XL

HARMONIZED STANDARD

ASTM D3578, ASTM D6124, ASTM D6124, EN455 1-4, EN21420:2020
ISO 13485:2016, ISO 9001:2015, FDA 21 CFR 177.2600



*this product contains natural rubber which may cause allergic reaction in some individuals. Discontinue use if encountered such problems and consult your physician.

