60LP

NATURAL RUBBER LATEX

POWDER FREE

Presenting 60LP, our best selling food handling gloves.

This gloves offers superior comfort for the user without compromising barrier protection and excellent gripping qualities.

This glove is also ideal for various application suited for various applications.

KEY FEATURES

SUPERIOR COMFORT EXCELLENT GRIP TEAR RISISTANT ELASTIC GLOVE EASY DONNING POWDER FREE

AVAILABLE SIZES

XS 5-6 S 6-7 M 7-8 L 8-9 XL 9-10

PRODUCT DESCRIPTION

6.0g, Powder Free Latex Glove, 240mm / 9"
Food Handling Glove
Palm Textured
Beaded Cuff
Single Use
Non Sterile

MATERIAL

Natural Latex Rubber

COLOR

Natural Latex Color / Tinge of Yellow



COMPLIANCE

Manufactured in ISO 9001 & ISO 13485 certified facility meeting ASTM and EN harmonised standards



RECOMMENDED FOR

- FOOD & BEVERAGES INDUSTRY
- JANITORIAL MAINTAENANCE
- OILY OR WET SURFACES
- FIRST RESPONDERS
- DOMESTIC USE
- AUTOMOTIVE
- PAINTING

DIMENSION AND SPECIFICATIONS

Item	XS	S	M	L	XL	Inspection Level
Hand Size	6	7	8	9	10	(AQL)
Width	75±5mm	85±5mm	95±5mm	105±5mm	115±5mm	S2
Glove	240mm	240mm	240mm	240mm	240mm	AQL 4.0
Length	minimum	minimum	minimum	minimum	minimum	
Cuff	0.08mm	0.08mm	0.08mm	0.08mm	0.08mm	
Thickness	±0.02mm	±0.02mm	±0.02mm	±0.02mm	±0.02mm	
Palm	0.10mm	0.10mm	0.10mm	0.10mm	0.10mm	S2
Thickness	±0.02mm	±0.02mm	±0.02mm	±0.02mm	±0.02mm	AQL 4.0
Finger Thickness	0.12mm	0.12mm	0.12mm	0.12mm	0.12mm	
	±0.02mm	±0.02mm	±0.02mm	±0.02mm	±0.02mm	
Weight	5.2g	5.6g	6.0g	6.4g	6.8g	
(Reference)	±0.2g	±.0.2g	±0.2g	±0.2g	±0.2g	

PHYSICAL PROPERTIES

	Standard	Before Ageing	After Ageing
Force at Break (N)	EN 455-2	min. 6N	min. 6N
Tensile Strength (Mpa)	ASTM D3578	min.18	min.14
Elongation (%)	ASTM D3578	min. 650	min. 500

OTHER PARAMETERS

Criteria	Inspection Level / AQL	Standard		
Pinholes	G1 / AQL 1.5			
Major Visual	G1 / AQL 2.5			
Powder Content	max. 2mg/glove	ASTM D6124		
Protein Content	max. 50ug/dm ²	ASTM D5712		





ORDERING INFORMATION

Size	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)
Code	60LP - XS	60LP - S	60LP - M	60LP - L	60LP - XL

HARMONIZED STANDARDS

ASTM D3578, ASTM D6124, ASTM D6124, EN455 1-4, EN21420:2020

ISO 13485:2016, ISO 9001:2015, FDA 21 CFR 177.2600

PACKING INFORMATION

100 pieces of gloves in a dispenser box OR bags 10 dispensers / bags in a shipping case

STORAGE CONDITION

Recommended to store in a cool and dry place with temperature below 30°C

SHELF LIFE

5 years



*this product contains natural rubber which may cause allergic reaction in some individuals. Discontinue use if encountered such problems and consult




















KGM GLOVES SDN. BHD. LOT 18893 & 18894, Jalan Perusahaan 9, Kawasan Perusahaan Kamunting, 34600, Kamunting, Perak, Malaysia. Tel: +605-891 3612

Website: www.kgmgloves.com Email: contact@kunng.com.my



