

62WH

POWDER FREE WHITE NITRILE MEDICAL • CLEANROOM

Depending on your needs, the 62WH Powder Free Disposable gloves can be processed as a medical examination / cleanroom gloves.

62WH processed to be a cleanroom glove offers superior static dissipation, low liquid particle count good thickness, handles solvents well.

This glove has also been tested for use in food handling.

KEY FEATURES

- Medical Device Class I / CLASS A (Low Risk)
- ISO Class V Cleanroom Glove
 - Available in C100 / C1000 / C10,000 and CC
 - Available in your preferred finishing Standard / Slippery / Non Tacky / High Tacky

DISPOSABLE NITRILE GLOVES
• MEDICAL EXAMINATION GRADE
• CLEANROOM APPLICATION

EXCELLENT BARRIER PROTECTION
LOW LIQUID PARTICLE COUNT
LOW IONIC COUNT
SILICONE FREE
PUNCTURE RESISTANT
ANTISTATIC GLOVE
GREAT ELASTICITY
GREAT TACTILITY
EXCELLENT GRIP
EASY DONNING
NON STERILE
LATEX FREE
SINGLE USE

AVAILABLE SIZES

XS 5-6	S 6-7	M 7-8	L 8-9	XL 9-10
--------	-------	-------	-------	---------



MDA Registration Number: GA1509421-79520
EU Type Examination carried out by CENTEXBEL, Belgium (CE 0493)
Module D Conformity Assessment carried out by SGS Firmko OY, Finland (CE 0598)

RECOMMENDED FOR

Healthcare

Healthcare Professionals
Veterinary Use
Skilled nursing Centers
Wound Care Centers
Pharmacies

Labs/Pharmaceutical

Diagnostic Testing Labs
Medical Compounding
Chemical Handling

Cleanroom Application

Disk Drive Assembly Line
Semiconductor
Electronics

First Responders

Law & Enforcement
Fire Fighters
Emergency Medical Services (EMS)

“Superb Static Decay Properties”



PRODUCT DESCRIPTION

6.2g, Translucent White Disposable Powder Free Nitrile
Gloves, 295mm
Examination Glove / PPE Cat III / Food Handling
Finger Tip Textured
Beaded Cuff
Single Use
Non Sterile

MATERIAL

Acrylonitrile Butadiene Copolymer Latex

COLOR

Translucent White

PACKAGING

100 pieces of gloves in a dispenser box OR bags
10 dispensers / bags in a shipping case

STORAGE CONDITION

Recommended to store in a cool and dry place with
temperature below 30°C

SHELF LIFE

3 years

DIMENSION AND SPECIFICATIONS

Item	XS	S	M	L	XL	Inspection Level
Hand Size	6	7	8	9	10	(AQL)
Width	75±5mm	85±5mm	95±5mm	105±5mm	115±5mm	S2 AQL 4.0
Glove Length	295mm minimum	295mm minimum	295mm minimum	295mm minimum	295mm minimum	
Cuff Thickness	0.08mm ±0.02mm	0.08mm ±0.02mm	0.08mm ±0.02mm	0.08mm ±0.02mm	0.08mm ±0.02mm	S2 AQL 4.0
Palm Thickness	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	0.10mm ±0.02mm	
Finger Thickness	0.16mm ±0.02mm	0.16mm ±0.02mm	0.16mm ±0.02mm	0.16mm ±0.02mm	0.16mm ±0.02mm	
Weight (Reference)	5.1g ±0.2g	5.5g ±0.2g	6.2g ±0.2g	6.5g ±0.2g	7.0g ±0.2g	

PERFORMANCE EVALUATION

Chemicals	ISO 374-1 / Type B Permeation Resistance	Breakthrough Time in (min)	EN 374-4 Degradation in (%)
J: Heptane	Level 6	>480	47.7
K: Sodium Hydroxide 40%	Level 6	>480	-25.6
T: Formaldehyde 37%	Level 6	>480	2.1

PHYSICAL PROPERTIES

	Standard	Before Ageing	After Ageing
Force at Break (N)	EN 455-2	min. 6N	min. 6N
Tensile Strength (Mpa)	ASTM D6319	min.14	min.14
Elongation (%)	ASTM D6319	500	400

OTHER PARAMETERS

Criteria	Inspection Level / AQL	Standard
Pinholes	G1 / AQL 1.5	
Major Visual	G1 / AQL 2.5	
Powder Content	max. 2mg/glove	ASTM D6124
Protein Content	N/A	ASTM D5712





CLEANROOM SPECIFICATION


Made available in Class-10, Class-100, Class-1000, Class-10,000 & Cleanroom Compatible gloves.

ORDERING INFORMATION

Size	XS (5.5-6)	S (6.5-7)	M (7.5-8)	L(8.5-9)	XL(9.5-10)
Code	62WH - XS	62WH - S	62WH - M	62WH - L	62WH - XL

HARMONIZED STANDARDS

ASTM D6319, ASTM D6124, EN455 1-4, EN420:2003 + A1:2009, EN 1186, EN 374 1-5, EN 16523-1
ISO 10993- 1:2018;5:2009; 10:2013, ISO 15223-1:2016, ISO 1041:2008 + A1:2013, ISO 16604:2004,
ISO 3071:2020, ISO 13485:2016, ISO 9001:2015, FDA 21 CFR 177.2600



Contact us for ordering or more information



KGM GLOVES SDN. BHD.
LOT 18893 & 18894
Jalan Perusahaan 9,
Kawasan Perusahaan Kamunting,
34600 Kamunting, Perak,
Malaysia.
Tel: +605-891 3612
Website: www.kgmgloves.com
Email: contact@kunng.com.my

