



It provides exceptional thermal conductivity, faster heat-up times, and outstanding heating efficiency.

Available in 550 mm width and 292, 452, and 1012 mm heights

Available in Gold, Granite, Sky Blue and Inox.

Rifle									
PRODUCT CODE	HEIGHT (MM)	WIDTH (MM)	DRY WEIGHT (KG)	BOXED WEIGHT (KG)	COLOR	VALVE AXIS (MM)	WALL - PIPE (MM)	BTU @DELTA50	ELECTRIC (WATT)
RFL2GOLD	292	550	4.2	5.5	GOLD	155	30	560	-
RFL2GRNT	292	550	4.2	5.5	GRANITE	155	30	560	-
RFL2SKYB	292	550	4.2	5.5	SKY BLUE	155	30	560	-
RFL2INOX	292	550	4.2	5.5	INOX	155	30	560	-
RFL4GOLD	452	550	7.3	9.4	GOLD	155	30	1120	-
RFL4GRNT	452	550	7.3	9.4	GRANITE	155	30	1120	-
RFL4SKYB	452	550	7.3	9.4	SKY BLUE	155	30	1120	-
RFL4INOX	452	550	7.3	9.4	INOX	155	30	1120	-
RFL8GOLD	1012	550	10.4	13	GOLD	155	30	2240	-
RFL8GRNT	1012	550	10.4	13	GRANITE	155	30	2240	-
RFL8SKYB	1012	550	10.4	13	SKY BLUE	155	30	2240	-
RFL8INOX	1012	550	10.4	13	INOX	155	30	2240	-

Our Commitment to Safe Installation

The Rifle has been engineered for safe and straightforward installation.

There are 2 round fixing pieces that is fixed on the wall and the radiator is fixed on those round pieces. Then to stabilize, the ex socket grub screw is screwed.

Designed in accordance with the principles of VDI 6036, the fixing system is engineered to provide long-term safety and stability under normal operating conditions.

For a safe installation, the installer is responsible for:

- Verifying that the supporting wall is suitable to support the filled radiator.
- Selecting fixings appropriate for the wall construction.
- Installing the radiator in accordance with the Modaheat installation instructions.
- Ensuring the radiator is securely fixed before commissioning.

Following these instructions will help ensure the safe, reliable, and long-lasting performance of your radiator.

