

JMA CONVEYOR CATALOGUE - FASTENER

OCT 2020 YEAR






Belt Fastener

- ✓ Strong and impact-resistant splice.
- ✓ Abrasion resistant splice.
- ✓ The front edge of the fastener is bevelled to allow it to interface smoothly with conveyor components.
- ✓ Fasteners are shipped inside carton boxes as 4 sets/box. Connecting pins are included in the boxes.

Type		Belt thickness	Remarks
	JMA-R5	9-16mm	Tensile strength: 1600N/mm
	JMA-R6	10-20mm	Tensile strength: 1800N/mm
	JMA-RV6	6-12mm	Tensile strength: 1000N/mm
	JMA-T10	7.5-9.5mm	Tensile strength: 1250N/mm
		9.5-12.5mm	
		12.5-14mm	
		14-16mm	
	JMA-T12	8-12mm	Tensile strength: 1600N/mm
		12-16mm	
	JMA-GL1000	5-10mm	Tensile strength: 1000N/mm
		7-12mm	

Type		Belt thickness	Remarks
	JMA-GL1400	8-13mm	Tensile strength: 1400N/mm
		10-15mm	
	JMA-GL2000	13-18mm	Tensile strength: 2000N/mm
		15-20mm	
	JMA-DGK4	7.5-9.5mm	Tensile strength: 1250N/mm
		9.5-12.5mm	
		12.5-14mm	
		14-16mm	
	JMA-2000	7.5-9.5mm	Tensile strength: 1400N/mm
		9.5-12.5mm	
		12.5-14mm	
		14-16mm	
	JMA-SK	6-9mm	Tensile strength: 1200N/mm
		10-12mm	
		6-9mm	Tensile strength: 1400N/mm
		10-12mm	
		12-14mm	
	JMA-PL	Customize	Size: 1"
			Size: 1-1/2"
			Size: 2"
			Size: 2-1/2"

Type	Name	Cable Dia.
	Normal string	6mm
		7mm
		8mm
	Stainless steel string	6mm
		7mm
		8mm
		9mm
	stainless steel string with Nylon plastic coat	7mm
		9mm



CONVEYOR
PRODUCTS



CONVEYOR PRODUCTS

EMAIL: Sales@jmaustralia.com.au

TEL: 1800 975 038

ADDRESS: Factory 5 / 7 Nevada Court,
Hoppers Crossing, 3029 VIC

WEBSITE: www.jmaustralia.com.au