CABRILLO SERIES CORE SELECT + 5.5mm 12 mil WL RIGIDCORE CLICK LVT



SPECIFICATIONS

SI ECHICATIONS			
Contruction:	Solid Luxury Vinyl Tile Consisting Of A Wear Layer, Printed Film, And 4.0mm Solid Core		
Installation Method:	Floating/Click		
Plank Size:	7"x48"		
Total Thickness:	5.5mm		
Pre-Attached Underlayment:	1.5mm Embossed IXPE Pad		
Wear Layer:	12 mil		
Finish:	Polyurethane Top Coating		
Texture:	Deep Embossing		
Sq Ft Per Carton:	31.07 Sq Ft		
Pieces Per Carton:	13		
Cartons Per Pallet:	40		
Composition:	Phthalate-Free Polyvinyl Chloride		

TESTING

Product Classification:	ASTM F1700	Class III, Type B, Embossed Surface Meets And Exceeds Passing Requirements
Radiant Panel:	ASTM E648	Meets And Exceeds Passing Requirements (Class 1)
Slip Coefficient:	ASTM D2047	Meets And Exceeds Passing Requirements
Resistance To Chemical:	ASTM F925	Meets And Exceeds Passing Requirements
Impact Acoustical:	ASTM E492	Exceeds Code Requirement of 54 IIC over 6" Concrete With A Rating Of 70 db
Static Load Limit:	ASTM F970	Meets And Exceeds Passing Requirements
Quality Managment:	ISO 9001	Meets And Exceeds Passing Requirements
Environmental Management:	ISO 14001	Meets And Exceeds Passing Requirements

INSTALLATION



Herringbone



Double Herringbone



Staggered



Basket Weave

INSTRUCTIONS



PRODUCT WARRANTY

Limited Warranty:
Lifetime Residential, 10 Year Light Commercial

Lifetime Warranty: Rips, Tears, Cracking, and Curling.





GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.