

Avalon Series: Wood + Stone: 2.5mm, 5mm Luxury Vinyl Planks and Tiles

Post Installation Maintenance

- Keep traffic to a minimum during the first 24 hours to allow the adhesive to fully cure.
- Light Foot traffic is fine after 24 hours. Regular traffic can be resumed after 48 hours.
- Keep furniture off the floor for 24 hours so the adhesive has adequate time to cure.
- Always protect the floor when moving heavy furniture and appliances. You do not want to gouge or tear the floor.
- Wait for a minimum of 7 days following installation before any wet-wash, or scrubbing the floor.
- Clean with a neutral pH cleaner, utilizing a red or white cleaning pad, following the cleaner manufacturer's guidelines or dilution and usage ratios. Use the minimum amount of water on the floor to facilitate the efficacy of the cleaner. Rinse well with clean water and remove all excess water. No need for stripping or waxing.
- Like any very high-quality resilient flooring material, flooring products can become slippery when wet. Allow for the floor to dry after cleaning.
- Keep the room temperature between 55° - 85° F for at least 48 hours after installation.

Regular Care

- Maintain room temperature between 55° - 85°.
- Always protect the floor when moving heavy objects to prevent permanent scratches or tears.
- Use appropriately wide floor protectors under each leg of tables, chairs, and any heavy furnishing to avoid permanent damage.
- Place walk-off mats at all exterior entrances (DO NOT use rubber-base mats ON the new LVT floors) they help protect the floor from intrusion from water, grease, sand, and asphalt residue.
- Use blinds or curtains during peak sunlight hours. Prolonged exposure from direct sunlight may cause volatile temperature variations, which may discolor or damage your floor.
- Do use solvent cleaners.
- Clean with a neutral pH cleaner, utilizing a red or white cleaning pad, following the cleaner manufacturer's guidelines or dilution and usage ratios. Use the minimum amount of water on



- the floor to facilitate the efficacy of the cleaner. Rinse well with clean water and remove all excess water. No need for stripping or waxing.
- Avoid one –step “mop and polish” products . Dishwashing liquids and oil-based cleaners. These may leave a residue which can attract dirt and dull your floor’s finish.
- Avoid cleaners that contain abrasives or solvents which may permanently damage the floor.
- All stain-forming and aggressive substances must be immediately removed from the surface of the floor to facilitate the efficacy of the cleaner.
- Rinse well with clean water and remove all excess water.
- No need for stripping or waxing.