

## SPECIFICATIONS

Overall Thickness:	3.0mm
Wear Layer:	Micro Reinforced Polymer
Edge Treatment:	Straight Edge
Warranty:	10 Year Heavy Commercial Warranty
Adhesive:	CPI Alliance™ and CPI Victory™ are the approved adhesives.
Maintenance:	Neutral Cleaner Only. No applied finishes, strippers or sealants.
Moisture Rating:	Up to 100% Rh when installed with proper adhesive.

## Caution

Condition in at least 19°C (67°F) or the normal temperature of the room where the product is to be laid, for at least 48 hours before installing. Cartons must be stacked less than 5 high and tiles removed 30 minutes before use. The site conditions must be maintained during installation and for at least 48 hours after completion.  CPI, LLC will not accept claims where these instructions have not been followed.

## TESTING

Test Item		Standard	HRC
Level of use		EN 685	33
Fraying		EN 1814	Frayproof
Thermal resistance		ISO 8302	0.02m²K/W
Castor chair resistance		EN 985	No damage
Dimensional stability		ISO 23999 EN 986	≤ 0.10% ( Norm: ≤ 0.25% ) Passed
Fire resistance		EN 13501-1	Bfl -s1
Indoor air quality			Low VOC (floor score certified)
Underfloor heating		EN 12524	Suitable
Light fastness		ISO 105-B02	≥ 6
Slip resistance		DIN 51130 EN 13893	R11 DS
Flexibility		ISO 24344	Passed
Impact sound insulation		ISO 10140-3	9dB
Body Voltage		EN 1815	≤ 2KV
Squareness & Straightness		ISO 24342 ASTM F2055	No deviation ≤ 0.01 in
Residual indentation		ISO 24343-1 ASTM F1914	≤ 0.1mm < 8%
Resistance to chemicals		ISO 26987 ASTM F925	No Defects No Defects

## MANUFACTURING

ISO 9001 Quality Management System  
ISO 14001 Environmental Management System  
OHSAS 18001 Occupational Health and Safety Management System

## GENERAL INFORMATION

For Pricing, Samples, Warranties, and Installation Guides, please contact us at [contact@catalinaproducts.international](mailto:contact@catalinaproducts.international) or call 714-716-1677.

\*50cm x 50cm Square Tile only available in HRC Prism  
\*\*25cm x 100cm Plank only available in HRC Herringbone, Melange, and Ombre

Certification



CERTIFIED BY SCS Global Services

OEKO-TEX®  
CONFIDENCE IN TEXTILES  
STANDARD 100

VALIDATED

