

HEAVY DUTY TILE



CATALINA
PRODUCTS
INTERNATIONAL

714.716.1667 | contact@catalinaproducts.international

SPECIFICATIONS

Overall Thickness:	3.0mm
Wear Layer :	20Mil with Integrated SRX Tech
Edge Treatment:	Straight Edge
Texture:	Smooth Touch Stippled Surface
Warranty:	15 Year Limited
Adhesive:	CPI Alliance, CPI Victory, And CPI Cambria
Maintenance:	Clean Sweep Technology No applied finishes, strippers or sealants
Moisture Rating:	Up to 100% Rh when installed with proper adhesive


SIZES

18" x 18" (45.72cm x 45.72cm)


Tiles Per Carton 16

Sq Ft Per Carton 36


INSTALLATION



Quarter Turn



Brick



Monolithic

TESTING

Test Item	Test Method	Results
Static Load Limit	ASTM F970	2,000psi
Squareness	ASTM F2055	Passes
Flexibility	ASTM F137	Passes
Dimensional Stability	ASTM F2199	Passes
Chemical Resistance	ASTM F925	Passes
Resistance to Light	ASTM F1515	Passes
Resistance to Heat	ASTM 1514	Passes
Fire Resistance	ASTM E648	Passes
Smoke Density	ASTM E662	Passes
Dynamic Coefficient of Friction	ANSI A326.3	0.43

MANUFACTURING

ISO 9001 Quality Management System
ISO 14001 Environmental Management System
OHSAS 18001 Occupational Health and Safety
Management System

AIR QUALITY

Low VOC
Floor Score
Certification



GENERAL INFORMATION

For Pricing, Samples, Warranties, and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1677.