

SUMMIT TURF



CATALINA
PRODUCTS
INTERNATIONAL

714.716.1667 | contact@catalinaproducts.international

TURF SPECIFICATIONS

Yarn #1 Type	Mattex Omega Monofilament
Color Name	Field Green/Apple
Total Denier	10,800(1800/6)
Thickness/Form	Approx. 360 micron.
Description	Proprietary PE Formulation for Superior Wear Resistance
Yarn #2 Type	Texturized Thatch
Color Name	Field Green/Jute
Total Denier	5000
Description	Texturized Monofilament PE Thatch
Total Yarn Face Weight	60 Oz. / SqYd
Primary Backing #1	Tencate K29, consisting of two warp knitted primaries woven into one
Primary Backing Weight	7 Oz. / SqYd
Secondary Coating	20 Oz. Urethane / SqYd
Total Product Weight	87 Oz. / SqYd

TUFTING SPECIFICATIONS

Pile Height	1 1/8" tufted, approx. 1" finished
Stitch Rate	AS REQUIRED
Tufting Gauge	3/8"
Roll Widths	15'
Drainage Perforations	STANDARD 3"x4" pattern

TENCATE BACKING SPECIFICATIONS

	Unit	Typical Value	Minimum	Maximum
Weight	g/m ²	250,0	236,5	263,5
Construction Fabric 1 MD	threads/10 cm	118	117	119
CD	threads/10 cm	71	70	72
Fabric 2 MD	threads/10 cm	118	117	119
CD	threads/10 cm	43	42	44
Strength (Fmax) MD	N/5 cm	1900	1650	
CD	N/5 cm	2850	2450	
Elongation at Fmax MD	%	20,0	15,0	25,0
CD	%	20,0	15,0	25,0
Shrinkage 132 MD	%	4,8		5,5
CD	%	2,0		2,5

Test methods are based from ISO 13934-1

GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.