# **VICTORY**<sup>TM</sup>

1-Part Moisture Barrier Adhesive for Resilient Flooring



### **PRODUCT BENEFITS**

- Simple 1-part system (modified urethane)
- Strong early grab, fast-curing formula
- High-strength, waterproof bond
- Self-leveling technology reduces telegraphing
  - LEED v4 contributing
  - VOC content 0.1 g/L (meets SCAQMD Rule 1168)
  - CDPH/EHLB Standard Method v1.2
  - Does not contain methylene chloride and perchloroethylene
- Contributes to low emitting materials

# **APPROVED FLOORING TYPES**

- HVT/LVT/LVP
- Sheet goods (vinyl, homogeneous, heterogeneous, fiberglass, felt-backed)
- Rubber (tile and sheet)
- Linoleum
- WPC/WSC
- Cork-backed hard surface
- Cork flooring
- Cork underlayment
- VCT/VET
- Stair treads (rubber and vinyl)

Resilient flooring has finally met its match. Victory's<sup>TM</sup> safe, 1-part chemistry makes it a faster, more install-friendly alternative to 2-part epoxy systems. Engineered for heavy rolling loads and challenging environments, Victory's<sup>TM</sup> waterproof design forms a robust moisture vapor barrier and can also take the punishment introduced by topical liquids.

NOW FEATURING NO MOISTURE TESTING

AVAILABLE IN 2-GALLON PAIL Shelf Life: 1 Year



## **APPLICATION METHODS**



150-260 sf/qt

Note: Coverage range dependent upon substrate composition and porosity, application method and flooring type.

### CERTIFICATIONS













12 Hours









