CABRILLO SERIES CORE 2.0mm 12 mil WL GLUE DOWN LVT



SPECIFICATIONS

Solid Luxury Vinyl Tile Consisting Of A Wear Layer, Printed Film, And 2.0mm Solid Core
Solid Editory Villyi The Consisting Of A Wear Layer, Timted Timi, And 2.0mm Solid Core
Glue Down
7"x48"
2.0mm
12 mil
Polyurethane Top Coating
Deep Embossing
51.34 Sq Ft
22
55
Phthalate-Free Polyvinyl Chloride

TESTING

Product Classification:	ASTM F1700	Class III, Type B, Embossed Surface Meets And Exceeds Passing Requirements
Radiant Panel:	ASTM E648	Meets And Exceeds Passing Requirements (Class 1)
Slip Coefficient:	ASTM D2047	Meets And Exceeds Passing Requirements
Resistance To Chemical:	ASTM F925	Meets And Exceeds Passing Requirements
Impact Acoustical:	ASTM E492	Exceeds Code Requirement of 54 IIC over 6" Concrete With A Rating Of 70 db
Static Load Limit:	ASTM F970	Meets And Exceeds Passing Requirements
Quality Managment:	ISO 9001	Meets And Exceeds Passing Requirements
Environmental Management:	ISO 14001	Meets And Exceeds Passing Requirements

INSTALLATION



Herringbone



Double Herringbone



Staggered



Basket Weave

INSTRUCTIONS



PRODUCT WARRANTY

Limited Warranty:

Lifetime Residential, 10 Year Light Commercial

Lifetime Warranty:
Rips, Tears, Cracking, and Curling.





GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.