ALLIANCETM

High-Moisture Pressure Sensitive Adhesive for Resilient and Carpet Flooring



PRODUCT BENEFITS

- Immediate access for light traffic (PSA)
- Color changing technology improves install accuracy
- High-strength, waterproof bond
- PSA performance with hard-set resilience
- LEED v4 contributing

NOW FEATURING NO MOISTURE TESTING

When it comes to ultimate

adaptability to numerous

flooring types, Alliance™

Breaking all the rules, this

saves time with its instant

revolutionary product

access to light traffic.

like surface tack.

Shelf Life: 2 Year

MADE IN THE USA

AVAILABLE IN 4-GALLON PAILS

Alliance™ provides the waterproof benefits of a hardset adhesive while

aggressively retaining PSA-

holds the market.

- VOC content 11 g/L (meets SCAQMD Rule 1168)
- CDPH/EHLB Standard Method v1.2
- Does not contain methylene chloride and perchloroethylene
- Contributes to low emitting materials

APPROVED FLOORING TYPES

- HVT/LVT/LVP
- Carpet tile (hard- and soft-backed)
- Sheet goods (vinyl, homogeneous, heterogeneous, fiberglass)
- Rubber (tile and sheet)
- WPC/WSC
- Cork-backed hard surface
- Cork underlayment
- VCT/VET
- Broadloom carpet (breathable and vinyl-backed)
- Carpet cushion to substrate
- Stair treads (rubber and vinyl)

APPLICATION METHODS



90-350 sf/gal



Note: Coverage range dependent upon substrate composition and porosity, application method and flooring type.

CERTIFICATIONS























