

CABRILLO SERIES

CORE OPTIMUM

6.0mm 20 mil WL RIGIDCORE CLICK LVT



CATALINA
PRODUCTS
INTERNATIONAL

714.716.1667 | contact@catalinaproducts.international

SPECIFICATIONS

Construction:	Solid Luxury Vinyl Tile Consisting Of A Wear Layer, Printed Film, And 4.5mm Solid Core
Installation Method:	Floating/Click
Plank Size:	7"x48"
Total Thickness:	6.0mm
Pre-Attached Underlayment:	1.5mm Embossed IXPE Pad
Wear Layer:	20 mil
Finish:	Polyurethane Top Coating
Texture:	Deep Embossing
Sq Ft Per Carton:	23.90 Sq Ft
Pieces Per Carton:	10
Cartons Per Pallet:	50
Composition:	Phthalate-Free Polyvinyl Chloride


TESTING

Product Classification:	ASTM F1700	Class III, Type B, Embossed Surface Meets And Exceeds Passing Requirements
Radiant Panel:	ASTM E648	Meets And Exceeds Passing Requirements (Class 1)
Slip Coefficient:	ASTM D2047	Meets And Exceeds Passing Requirements
Resistance To Chemical:	ASTM F925	Meets And Exceeds Passing Requirements
Impact Acoustical:	ASTM E492	Exceeds Code Requirement of 54 IIC over 6" Concrete With A Rating Of 70 db
Static Load Limit:	ASTM F970	Meets And Exceeds Passing Requirements
Abrasion Resistance:	ASTM D3389	Meets And Exceeds Passing Requirements
Light Resistance:	ASTM F1515	Meets And Exceeds Passing Requirements
Heat Resistance:	ASTM F1514	Meets And Exceeds Passing Requirements
STC:	-	61
IIC:	-	66
Quality Management:	ISO 9001	Meets And Exceeds Passing Requirements
Environmental Management:	ISO 14001	Meets And Exceeds Passing Requirements


INSTALLATION



Herringbone



Double
Herringbone



Staggered



Basket
Weave

INSTRUCTIONS



PRODUCT WARRANTY

Limited Warranty:

20 Year Residential, 5 Year Light Commercial

Lifetime Warranty:

Rips, Tears, Cracking, and Curling.



GENERAL INFORMATION

For Pricing, Samples, Warranties and Installation Guides, please contact us at contact@catalinaproducts.international or call 714-716-1667.