

## SPECIFICATIONS

|                    |  |
|--------------------|--|
| Overall Thickness: | 2.5mm  |
| Wear Layer :       | Micro Reinforced Polymer 20Mil                                   |
| Edge Treatment:    | Straight Edge  |
| Texture:           | Nano "Tick" Finish   |
| Warranty:          | 10 Year Limited  |
| Adhesive:          | CPI Alliance, CPI Victory, And CPI Cambria                       |
| Maintenance:       | Neutral Cleaner Only. No applied finishes, strippers or sealants |
| Moisture Rating:   | Up to 100% Rh when installed with proper adhesive                |
| Construction:      | Four core hetero laminate  |

## SIZES


18" x 18" (45.72cm x 45.72cm)

Tiles Per Carton 16  
Sq Ft Per Carton 36


## INSTALLATION



Quarter Turn



Brick



Monolithic

## TESTING

| Test Item                       | Test Method | Results  |
|---------------------------------|-------------|----------|
| Static Load Limit               | ASTM F970   | 2,000psi |
| Squareness                      | ASTM F2055  | Passes   |
| Flexibility                     | ASTM F137   | Passes   |
| Dimensional Stability           | ASTM F2199  | Passes   |
| Chemical Resistance             | ASTM F925   | Passes   |
| Resistance to Light             | ASTM F1515  | Passes   |
| Resistance to Heat              | ASTM 1514   | Passes   |
| Fire Resistance                 | ASTM E648   | Passes   |
| Smoke Density                   | ASTM E662   | Passes   |
| Dynamic Coefficient of Friction | ANSI A326.3 | 0.43     |

## MANUFACTURING

ISO 9001 Quality Management System  
ISO 14001 Environmental Management System  
OHSAS 18001 Occupational Health and Safety Management System

## AIR QUALITY

Low VOC  
Floor Score  
Certification



CERTIFIED BY  
SCS Global Services

(1): Made in America; materials are produced manufactured in Ohio. In some cases where supply chain issues exist, materials may be source elsewhere.

## GENERAL INFORMATION

For Pricing, Samples, Warranties, and Installation Guides, please contact us at [contact@catalinaproducts.international](mailto:contact@catalinaproducts.international) or call 714-716-1677.