

SV-MMM Mobile Mud Mover

- O Accommodates 50mm, 75mm, 100mm Pumps
- O Pump Rotates 180 Degrees
- O Vacuum Load Material From 50Mtr+
- O Discharge To On-board Slops Tank





U1/5-7 Boeing Place - Caboolture - QLD 4510 - Australia

+61 456 000 665 / info@solidsvac.com / www.solidsvac.com

SV-MMM

Mobile Mud Mover

The SV-MMM is a highly versatile unit capable of fulfilling several roles including, vacuum excavation, sump maintenance, spill response and flood remediation works. With the ability to recover solids laden sludges and slurry from over 50 metres via vacuum and deliver the same into the on-board slops tank or to any point within 500 metres.

The MMM combines a Solidsvac pump with a 316 vessel and valves which requires no priming and has no internal moving parts. It can't be damages by dry running and can lift a slurry over 12 metres vertically. The MMM can be equipped with either an SV40 50mm (2"), SV60 or SV70 75mm (3") or an SV100 100mm (4") vacuum loading solids pump.

- Hot dipped galvanised tandem trailer with LED work lights, load ramps, toolbox, hose storage, traffic cone storage and 3 spare tyres.
- Steel 750 Litre Easy Empty Slops Tank
- Silenced 185cfm Diesel Compressor (European 5 Year warranty)
- SV60-SP Vacuum Loading Solids Pump (100cfm Standard)
- SS Suction Wand and Duck Bill Vacuum Head Attachment
- Secure hose storage rack

 NOTE: The Solidsvac pump can be removed from trailer and wheeled to location if required.

TECHNICAL DATA	METRIC	US IMPERIAL
Length	6400 mm	21' 6"
Width	1950 mm	6' 5"
Height	2050 mm	5' 7"
Tare Weight	2165 kg	4773 lb
ATM	2800 kg	6172 lb
Slops Tank Capacity	750 ltr	198 gal
Compressor Supply	5.09 m³/min	180 cfm



GENERAL USAGE

- Mining
- Civil Construction
- O Industrial
- O Municipal

APPLICATIONS INCLUDE

- Sump Cleaning
- Vacuum Excavation
- Spill Response
- O Flood Remediation
- O Trenching
- O Potholing
- O Drain Cleaning

OPTIONAL ACCESSORIES

- O Dewatering Screen
- O Drop Box (Skip Discharge)