

SV70-SP Vacuum Loading Solids Pump

- **O** Heavy Duty
- O Air Operated-Vacuum Loading
- **O** High Solids Content Transfer



U1/ 5-7 Boeing Place - Caboolture - QLD 4510 - Australia

+61 456 000 665 / info@solidsvac.com / www.solidsvac.com

SV70-SP Vacuum Loading Solids Pump

The Solidsvac SV70-SP is designed to reliably handle any flowable sludge and slurry and is ideally suited where submersible, centrifugal and diaphragm pumps are not a viable option.

Designed to offer the operator a one man vacuum recovery pressure discharge unit capable of recovering and transferring almost any flowable material, the extra heavy duty twin 75mm (3") suction and discharge rotary ball valves deliver outstanding performance in the capture and transfer of heavy flowable sludges with high solids content.

100% air powered, the all new compact, fully automatic, robust and fully mobile SV70-SP, generates 22.5"Hg+ of vacuum and can be used in a wide range of applications including mining and industrial.

TECHNICAL DATA	METRIC	US IMPERIAL	GENERAL USAGE
Height	1150 mm	45″	O Mining
Width	650 mm	25.5″	O Drilling
Length	1430 mm	56.3″	O Industrial
Weight	120 kg	264 lb	• Agricultural
Air inlet	13 mm	1/2" BSP	O Municipal
Suction inlet	75 mm	3″	APPLICATIONS INCLUDE
Discharge outlet	75 mm or 100 mm	3" or 4"	O Drilling mud waste
Suction lift	7.9m @ 100 cfm 9.2 @ 180 cfm 11.5m @ 230 cfm	26' 2" @ 100 cfm 30' @ 180 cfm 37' 7" @ 230 cfm	 O Corrosive slurries O Noxious waste O Mine tailings
Air consumption options	2.8 m³ /Min Jetpack 5.0 m³ /Min Jetpack 6.5 m³ /Min Jetpack	100 cfm Jetpack 180 cfm Jetpack 230 cfm Jetpack	O Raw effluent OPTIONAL ACCESSORIES
Delivery	400+ m	1312+ ft	O Suction wand
Displacement cycle	65 ltr	17 gal	O Suction hose
Operating pressure	7 bar (max) @ 690 kPa 4.5 bar (min) @ 448 kPa	102 psi (max) 65 psi (min)	 Discharge hose Duck bill & vacuum head
Maximum solids	50 mm	2"	 O Duck bill & vacuum head O Large capacity strainer
Measured water throughput	400 lpm	106 gpm	O Dropbox

0

Delivery carousel

O Vessel and valves manufactured in 316 stainless steel

• Individually adjustable load and discharge cycles



U1/ 5-7 Boeing Place - Caboolture - QLD 4510 - Australia

+61 456 000 665 / info@solidsvac.com / www.solidsvac.com