QUICK REFERENCE CHEMICAL GUIDE

ON DRAIN & FILL/ START UP

- 1. Pour 8 oz. of Metal Gon into freshly filled hot tub water.
- 2. Ensure FROG System Bromine & Mineral Cartridges do not need replacing.
- 3. Boost your start-up with a onceper-week spa shock treatment of Spa 56 (Sodium Dichlor) or Sodium Bromide.

ROUTINE MAINTENANCE

- 1. Test your water 1 –2 times per week with test strips.
- 2. Shock after each use or at least once per week with Spa 56 (Sodium Dichlor) or Sodium Bromide.
- 3. Add 1-2 ounces of spa clarifier & spa de-scaler per week.
- 4. If you have a FROG System installed, change your Bromine cartridge every 6 weeks and mineral cartridge every 4 months (or when either is empty).
- 5. Rinse filter cartridges every 1-2 weeks with a high pressure hose.

CONTACT INFORMATION

SUNBELT HOT TUBS, LLC

Website:	www.sunbelthottubs.com
Phone:	1-800-258-7727 (SPAS)
Email:	info@sunbelthottubs.com

AFTER SALES SUPPORT

Website:	www.sunbelt.parts
Phone:	281-788-6709
Email:	parts@sunbelt.parts

WARRANTY REGISTRATION

Please register you product and find warranty coverage details at: www.sunbelthottubs.com/warranty

Email:

Registration@sunbelthottubs.com



Start Enjoying Life! Since 1979





Start Enjoying Life! Since 1979

QUICK START GUIDE

> FOR PORTABLE HOT TUBS

START-UP PROCEDURE

Once the hot tub is delivered and installation is complete, the next step is to fill it and heat the water.

IMPORTANT: It is recommended to perform the following procedure when you drain and refill the spa, to protect the heater element.

- Power must be turned OFF at the circuit breaker and at the G.F.C.I., before you start.
- Open the access door and inspect all fittings to ensure they are tight and slide-valves are fully extended.
- Fill the tub, using your garden-hose, to the proper water level.
- To apply power, push the RESET (ON) button at the G.F.C.I. & reset the circuit breaker to the ON position.
- Push the "Jets" button on the control panel, activating the high speed pump. Keep pump running for at least three minutes to purge the air out of the plumbing.
- Once air bubbles stop coming out of the jets and the pump is primed, select the desired temperature.

QUICK START GUIDE

In a hurry to jump in? Please read the basic setting instructions below. Your hot tub comes with universal default settings. If you keep these settings, you only need to remember the steps in setting the temperature and then pressing the SET key when you are done using the hot tub.

The in-depth version of this manual will explain the function of each of the keys on the control panel, how to change programmed settings, and what each setting does. It will also explain the error messages you may encounter, their significance, and how to correct them. This comprehensive manual can be found at www.sunbelthottubs.com/manuals.

SETTING TEMPERATURE

1. Press and hold the UP (TEMP) key for 2 seconds. The display will flash the current selected temperature. 2. Using the UP or DOWN arrow keys, scroll to the desired temperature.

3. Press the SET key to lock in the new temperature.

The controller will lock in the new temperature and then display the current temperature. Not pressing the SET key after entering your desired temperature will cause the hot tub to revert to the previous setting. Your selection will not be saved.

IMPORTANT: Always turn down the heat BEFORE you drain the hot tub.

THE SET KEY

After using the hot tub, press the SET key to tell the microcontroller you are done using the spa. It will then take over the spa's management, including the different filtration cycles, heat maintenance, economy modes and protection against freezing.



