
# Product Datasheet

**Commodity：** Double-Ended Metal Halide Lamps

**Specifications Model：** MH-DE 150/NDL



**Description ：**
Ignitor Pluse Start

| | | | |
|---|---|---|---|
| **Electrical** | | | |
| 1 | Rated Wattage [W] | | 150W |
| 2 | Rated Voltage [V/Hz] | | / |
| 3 | Power Factor | | / |
| **Product Parameters** | | | |
| 4 | Luminous flux [lm] | | 12000lm |
| 5 | Lumen efficacy [lm/W] | | 80lm/w |
| 6 | Luminosity [Lux] | | / |
| 7 | Beam angle [°] | | 360° |
| 8 | Colour Temperature | | 4000K |
| 9 | Colour Rendering Index (Ra) | | 80 |
| 10 | Rated life [hrs] | | 9000 hrs |
| 11 | Lamp size<br>RX7s base<br><br> | Diameter D [mm] | D: 23mm |
| | | Length L [mm] | L: 138mm |
| 12 | Base | | RX7s |
| 13 | Dimmability | | No |
| 14 | Burning Position | | Horizontal ± 15° |

**Standard Compliance**

CE RoHS Compliance

## Usage Instructions

1. To ensure the product functions properly, please make sure the apply voltage is within the specific range.
2. Install and use the product according to the proper methods.
3. Disconnect the power supply during installation or removal to avoid the risk of electric shock.
4. To ensure optimal performance, do not use the product in high humidity or dusty environments, including but not limited to: bathrooms, saunas, or grinding workshops.
5. Avoid staring directly at the light source for extended periods, as high-intensity light may cause eye damage.
6. The lamp shall be operated only in a luminaire with a protective shield.