Product Datasheet


Commodity： Double-Ended Metal Halide Lamps

Specifications Model： MH-DE 70/NDL



Description ：
Ignitor Pluse Start

Electrical

1	Rated Wattage [W]		70W
2	Rated Voltage [V/Hz]		/
3	Power Factor		/
Product Parameters			
4	Luminous flux [lm]		5500lm
5	Lumen efficacy [lm/W]		79 lm/w
6	Luminosity [Lux]		/
7	Beam angle [°]		360°
8	Colour Temperature		4000K
9	Colour Rendering Index (Ra)		80
10	Rated life [hrs]		9000 hrs
11	Lamp size RX7s base  	Diameter D [mm]	D: 20mm
		Length L [mm]	L: 120mm
12	Base		RX7s
13	Dimmability		No
14	Burning Position		Horizontal ± 15°

Standard Compliance

CE RoHS

Usage Instructions

1. To ensure the product functions properly, please make sure the apply voltage is within the specific range.
2. Install and use the product according to the proper methods.
3. Disconnect the power supply during installation or removal to avoid the risk of electric shock.
4. To ensure optimal performance, do not use the product in high humidity or dusty environments, including but not limited to: bathrooms, saunas, or grinding workshops.
5. Avoid staring directly at the light source for extended periods, as high-intensity light may cause eye damage.
6. The lamp shall be operated only in a luminaire with a protective shield.