



PRE-INSULATED VOLUME CONTROL DAMPER







PRE-INSULATED VOLUME CONTROL DAMPERS RECTANGULAR

Introduction

Metal Tech Pre-insulated Volume Control Dampers are designed to control Air Flow inside Pre insulated Duct works of all pressure class to help to maintain the desired flow of air in HVAC System.

Our Pre-insulated Volume Control Dampers are Factory Tested for its Performance and Integrity.

Description

Damper body constructed from Pre Insulated Sandwich Panels with Aluminum embossed both sides of 80/80 Microns. Galvanised double skin Roll Formed Profiles are used for Blades. As per the requirements damper blades can be adjusted and locked to open/close intermediate position by rotating the Hand Locking GI Quadrant with locking Pin. Quadrant frames have measuring scale to understand exact position of the damper blade. Multiple regulating aerofoil blades coupled with high quality nylon gears to provide opposed blade open/close operation. The product is recommended for all type of pressure classification.

Construction Details

Body: 20mm Pre-Insulated Sandwich Panels

with both side embossed with 80/80 Microns Aluminum Stucco Sheets.


Blades: Galvanised Double Skin Aerofoil Blades

Gears and Spindle: High Quality Nylon

Quadrant: Galvanised Sheet Metal Quadrant with hand Locking Mechanism and Blade position Indicator.


Our Speciality: Both sides of our dampers are additionally provided with GI sheet metal for smooth movement of Blades and proper positioning of bushes and blade shafts.

DIMENSIONAL DRAWING



In Line Operation Performance characteristics diagram for Pre-insulated Volume Control Dampers Model MT-PIR-VCD

| PRESSURE DROP ACROSS LOUVER | | AIR VELOCITY (FACE*) | |
|-----------------------------|----|----------------------|-------|
| IN. H20 | PA | FPM | M/8 |
| 0.005 | 1 | 479 | 2.43 |
| 0.010 | 2 | 675 | 3.43 |
| 0.020 | 5 | 1187 | 6.03 |
| 0.030 | 7 | 1423 | 7.23 |
| 0.040 | 10 | 1773 | 9.01 |
| 0.050 | 12 | 2010 | 10.21 |
| 0.060 | 15 | 2184 | 11.09 |
| 0.080 | 20 | 2415 | 12.27 |
| 0.100 | 25 | 2699 | 13.71 |
| 0.120 | 30 | 2900 | 14.73 |



PRODUCTION ORDER FORMAT : MODEL -WIDTH (MM)X HEIGHT(MM)-QTY (NOS)





METAL TECH INDUSTRIES WLL

Bldg 970.Block 952,Road 5218, Ras Zuwayed

Post Box 10995, Kingdom of Bahrain

TEL: 77315555, FX:77314444,

Cell: 39646453, 32346666, 38766940,39998423

sales@metaltechbahrain.com

| OUR ACTIVITIES | | | |
|-----------------------------|------------------------------|--|--|
| HVAC DUCT MANUFACTURING | ACOUSTIC /THERMAL INSULATION | | |
| HVAC DUCT INSTALLATION | FIRE RATED DUCTS | | |
| HVAC AIRCONTROL ACCESSORIES | STAINLESS STEEL DUCTS | | |
| ALUMINUM CLADDING | | | |