# **LEGACY "BEST" SPRAY GUN**

Legacy Ergonomically designed to be the most comfortable





■ PSI: 5000

■ GPM: 12

■ Temperature: 300°F

■ 3/8" FPT Inlet x 1/4" FPT Outlet

Weight: 21 oz.

PART NO. **8.751-213.0** S "Best" Spray Gun

8.701-673.0

DESCRIPTION

Unitized Valve Kit

# **LEGACY "INDUSTRIAL" SPRAY GUN**



Featuring a comfortable grip to reduce user fatigue.



- PSI: 5000
- GPM: 10.4
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 19.84 oz.

PART NO.

**DESCRIPTION** 

8.751-214.0 "Industrial" Spray Gun

8.751-119.0

# Valve Kit

## **MV925 TRIGGER GUN**

Economical easy pull trigger gun.



- PSI: 4500
- GPM: 8
- Temperature: 320°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 16.08 oz.

PART NO.

**DESCRIPTION** 

8.754-907.0

MV925

## **M407 TRIGGER GUN**



- PSI: 4000
- GPM: 7
- Temperature: 250°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 13.4 oz.

PART NO. DESCRIPTION

8.750-247.0 M407 Trigger Gun

# **ECONOMY TRIGGER GUN**







- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" Female Inlet x 1/4" Outlet
- Weight: 23 oz.
- Private Label this Gun Ask your sales rep

PART NO. **DESCRIPTION** 9.113-082.0 A+ Trigger Gun

9.113-100.0 Unitized Valve Kit

# A+ RELAXED TRIGGER GUN





- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" Female Inlet x 1/4" Outlet
- Weight: 23 oz.
- Private Label this Gun Ask your sales rep

PART NO. **DESCRIPTION** 

9.117-659.0 A+ Relaxed Trigger Gun

#### A+ GUN





- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" Female Inlet x 1/4" Outlet
- Weight: 23 oz.
- Private Label this Gun Ask your sales rep

PART NO. DESCRIPTION

9.117-524.0 A+ Relaxed Trigger Gun

with Stainless Steel Swivel

SUTTNER W

## **GIANT TRIGGER GUNS**

The original "heavy-weight".`





- PSI: 5000
- GPM: 10
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 29.28 oz.

PART NO.	DESCRIPTION
8.710-394.0	S 21290C - Brass Outlet
8.710-392.0	\$ 21250B - Stainless-Steel Outlet
8.722-172.0	Repair Kit for Giant 212990C

# CERAMIC UNITIZED BALL VALVE SUTTNER W



- Ceramic Ball
- Highly Resistant Against Nearly All Soaps and Acids
- Fits in ST-2300, 2305, 2605, 2700 Spray Guns as a Repair Kit

PART NO.	DESCRIPTION
8.749-907.0	Ceramic Unitized Ball Valve

# ST-2720 SUTTNER TRIGGER GUN SUTTNER W

Designed for operators and applications with longer periods of cleaning time. Featuring the Relax-Action™ German engineered technology reduces trigger pulling force by 40% and holding force up to 90% compared to usual competitors spray gun.



- PSI: 1800
- GPM: 21.0
- Temperature: 300°F
- 3/8" Female NPT Inlet x 1/4" Female NPT Outlet
- Weight: 20 oz.

PART NO.	DESCRIPTION	
8.723-667.0	ST-2720 Gun	

# ST-2305 SUTTNER TRIGGER GUN SUTTNER W

Easy pull trigger.



- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 16.22 oz.

PART NO.	DESCRIPTION
8.758-457.0	ST-2305 Spray Gun, Safety Orange

# **ST-810 SUTTNER TRIGGER GUN**

Excellent for truck and fleet washing applications.





■ GPM: 8

■ Temperature: 320°F

■ 3/8" FPT Inlet x 1/4" FPT Outlet

■ Weight: 19.5 oz.

PART NO. DESCRIPTION 8.710-372.0 ST-810 Gun

# ST-2605 SUTTNER TRIGGER GUN SUTTNER W

Relax action design.



- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 21 oz.

PART NO.	DESCRIPTION
8.710-376.0	ST-2605
8.701-673.0	Unitized Valve

# ST-2305 SUTTNER TRIGGER GUN

Extreme durability with easy pull trigger and ceramic ball in valve for higher chemical resistance.



- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 21 oz.

PART NO.	DESCRIPTION
8.710-386.0	ST-2305
8.701-673.0	Unitized Valve
8.701-674.0	Unitized Weep Valve

# ST-2000 SUTTNER TRIGGER GUN SUTTNER W

15° offset angle thru gun for easier overhead use. The handle style for "Big Hands".



- PSI: 5000
- GPM: 10.4
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 26 oz.

PART NO.	DESCRIPTION
8.710-388.0	ST-2000
8.751-119.0	Unitized Valve - 5000 PSI
8.701-665.0	Unitized Weep Valve

# ST-1500 SUTTNER TRIGGER GUN SUTTNER W

The perennial favorite for general pressure washer applications.



- PSI: 5000
- GPM: 10.4
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 20.5 oz.

PART NO.	DESCRIPTION
8.710-384.0	ST-1500
8.710-385.0	ST-1500 with Weep
8.751-119.0	Unitized Valve - 5000 PSI
8.701-665.0	Unitized Weep Valve

# ST-2700 SUTTNER TRIGGER GUN SUTTNER W

Relax action design, stainless-steel gun.



- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 21 oz.

PART NO.	DESCRIPTION
8.710-389.0	ST-2700
8.701-658.0	Unitized Valve

# ST-2315 SUTTNER TRIGGER GUN SUTTNER W



Extreme durability with easy pull trigger.



- PSI: 5000
- GPM: 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 20.8 oz.

PART NO.	DESCRIPTION	
9.106-073.0	ST-2315, Ceramic Ball Valve for Chemical and Acid Resistance	

# **PA TRIGGER GUN**

Great for truck and fleet wash.





- PSI: 3200
- GPM: 8
- Temperature: 320°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 10 oz.

PART NO.	DESCRIPTION	
8.710-440.0	RL20	

Compact feel for smaller hands.





- PSI: 5000
- GPM: 10.5
- Temperature: 320°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 26 oz.

PART NO.	DESCRIPTION
8.710-377.0	RL30-YG5000
8.704-616.0	Repair Kit



- PSI: 5000
- GPM: 10.5
- Temperature: 320°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 27.5 oz.

PART NO.	DESCRIPTION
8.710-378.0	Vega 5000
8.704-615.0	Repair Kit

Easy pull and easy to hold with matching blue lance.





- PSI: 5650
- GPM: 8
- Temperature: 320°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 23.3 oz.
- Blue Vent Grip, Stainless-steel Lance has 1/4" BSP Threads





PART NO.	DESCRIPTION
9.802-227.0	RL-56 Blue Gun and Wand (nozzle protector not included)
8.710-446.0	RL-56 Blue Gun
8.710-645.0	40" Stainless-Steel Lance, blue vent grip (with nozzle protector)
8.704-610.0	Repair Kit, RL-55/RL-56

RL-56 Gun

mecline

# **PA LINEAR GUN**

Ergonomic design minimizes fatigue for operator.



- PSI: 4500
- GPM: 10.5
- Temperature: 320°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 19.2 oz.

PART NO.	DESCRIPTION
8.752-080.0	PA Linear Gun
9.801-398.0	PA Linear Gun Repair Kit

# **ML320**

Excellent light-duty gun.



- PSI: 2320
- GPM: 6.6
- Temperature: 212°F
- 1/4" M Inlet x 1/4" F Outlet
- Weight: 8.82 oz.

PART NO.	DESCRIPTION
8.757-839.0	ML320

# **SUTTNER TRIGGER GUN**

15° offset angle thru gun for easier overhead use.



- PSI: 4000
- GPM: 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet

SUTTNER W

■ Weight: 23 oz.

PART NO.	DESCRIPTION
8.710-370.0	ST-601
8.751-119.0	Unitized Valve - 5000 PSI

# **GP LOCKING TRIGGER GUN**

Rear Entry Spray Gun, Locking Trigger.





- PSI: 5000
- GPM: 10.5
- Temperature: 320°F
- 3/8" NPT-F Inlet x 1/4" NPT-F Outlet
- Weight: 22.4 oz.

PART NO.	DESCRIPTION
9.113-653.0	DGE5010SL

# **BIG GUN**



- PSI: 3200
- GPM: 53
- Temperature: 210°F
- 3/4" FPT Inlet x 1/2" FPT Outlet
- Weight: 47.5 oz.



- PSI: 7250
- GPM: 21
- Temperature: 210°F
- 1/2" Stainless-Steel FPT Inlet / Outlet
- Weight: 60.3 oz.

#### Model RL84 "Big Black Gun"

PART NO.	DESCRIPTION
8.740-165.0	Model RL204
8.749-327.0	Repair Kit - Model RL204
8.710-445.0	Model RL84
8.750-459.0	Repair Kit - RL84

# **OPEN GUNS**

Flow through design offers less downtime for repair

# **AP1000 OPEN GUN**

Durable glass reinforced handle. Tubular flow-thru intervals for high pressure and efficiency.



- PSI: 4000
- GPM 12
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 16.7 oz.

PART NO.	DESCRIPTION
8.710-396.0	AP1000 Open Gun
8.750-951.0	AP1000 Weep Gun with Blue, Lock

## **MV 925 OPEN GUN**

Just plain comfortable!



- PSI: 4060
- GPM 8
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 12.3 oz.

PART NO.	DESCRIPTION
8.754-988.0	MV925 without trigger

## ST-1500H OPEN GUN





- PSI: 5000
- GPM 10.4
- Temperature: 300°F
- 3/8" FPT Inlet x 1/4" FPT Outlet
- Weight: 20.5 oz.

**PART NO. DESCRIPTION 8.710-383.0** ST-1500 Open Gun

# **FLOW-THRU GUN**



PART NO.	DESCRIPTION	
8.710-400.0	Full Black Grip 3/8" FPT x 1/4" FPT	
GUN HANDLE WITH 18" LANCE		
8.710-403.0	Slim Red Grip 1/4" M x 1/4" F	
8.710-404.0	Full Red Grip 3/8" F x 1/4" M	

# **AP DUMP GUN**



Water continues to run through the tube even when trigger gun is closed.



PART NO.	DESCRIPTION	WEIGHT
8.710-405.0	Dump Gun 16" Lance	45.15 oz.
8.710-406.0	Dump Gun 40" Lance	59.61 oz.
8.704-169.0	Repair Kit	



PART NO.	DESCRIPTION
8.710-408.0	Dump Gun with 36" Barrel
8.700-311.0	Repair Kit

# **DUAL LANCES**

Dual lances allow for easy switching between high pressure cleaning and low pressure chemical application (chemical injector required). Stainless steel pipes give increased life when applying variable Ph products.

# **VP DUAL LANCE**

Superlite stainless-steel with nozzle guard and 1/4" stainless-steel outlet tubing.



- PSI: 4000
- 1/4" stainless steel tubes
- Fully insulated

■ Forged Brass Valve Body with stainless steel valve bushing

PART NO. **DESCRIPTION 8.711-308.0** \$\inf\$ 41"

# **DUAL LANCES**

Interpump Dual Lance. Excellent for downstream injector and zinc-plated for chemical resistance.





### **Dual Lance**

- GPM: 10.5
- Temp: 284°F
- Adjustment
- 1/4" Male Inlet
- 1/4" Dual Outlet
- **Deluxe Dual Lance**
- GPM: 10.5
- Temp: 284°F
- Side Handle Valve Side Handle Valve 1/4" QC Nozzle Adjustment
  - 1/4" Male Inlet
  - 1/4" Dual Outlet
  - 1/4" QC Brass Coupler, Brass Soap Nozzle

- **Dual Vented Lance**
- GPM: 10.5
- Temp: 284°F
- Holder
- 1/4" Soap Nozzle included
- 1/4" MPT inlet \*(Does not include male inlet QC

#### PART NO. DESCRIPTION **DUAL LANCE** 8.710-612.0 36" Standard 8.710-621.0 72" Extended **DELUXE DUAL LANCE** 8 904-281 0 72" Deluxe Extended **DUAL VENTED LANCE** 9.114-032.0 36" Dual Vented REPAIR KIT 8.900-135.0 Valve Repair Kit

# **DUAL LANCES**



#### AL 333 Basic Lance

- 3650 PSI
- GPM: 10.5
- Temperature: 300°F
- 1/4" Male Inlet
- 1/4" F NPT Dual Outlets
- 40" Molded Grip
- 1/8" Zinc-plated Tubes

# **AL344LS VP Lance**

- 4000 PSI
- GPM: 10.5
- Temperature: 302°F
- 1/4" Male Inlet
- Stainless Steel Seat & 40" Vented Grip
- 1/4" Stainless-steel Tubes
- 1/4" & 1/8" F NPT **Dual Outlets**
- (QC nozzles not included)

## AL344LS VPKIT - Premium

■ Includes: 1/4" OC & Soap Nozzle, Nozzle Protector and Valve Cover

# AL344LS VPKIT - Standard

Nozzle Protector and Valve Cover only

PART NO.	DESCRIPTION	
<b>DUAL LANCE</b>		
8.710-724.0	40 " AL333 Basic Dual Lance	
8.710-722.0	40" AL344LS-VPKIT Standard Dual Lance	
8.904-360.0*	40" AL344LS-VPKIT Premium Dual Lance with 1/4" QC Brass Inlet Plug	
REPAIR KIT		
8.720-548.0	AL333 Repair Kit	
9.803-267.0	AL344 Repair Kit	
*Model includes a hardened-steel QC inlet plug.		





# **SUTTNER DUAL LANCES**

SUTTNER 🧶

High-pressure, thin-wall tubing and zinc / chromate finish.



#### ST-54 with Side Handle

#### ST-53 with Knob

PSI: 4000 or 4500

■ GPM: 10

- 38" Total Length, Molded Grip
- Temperature: 300°F
- Weight: 42 oz.

PART NO.	DESCRIPTION	
8.710-613.0	ST-53 with Knob (4000 PSI)	
8.710-614.0	ST-54 with Side Handle (4500 PSI)	
8.701-594.0	Repair Kit (ST-53)	
8.900-153.0	Clamp Kit (ST-53/54)	
8.701-602.0	Repair Kit (ST-54)	

# **44" ZINC PLATED WAND**

Includes: Coupler and handle..

- PSI: 5000
- Temperature: 300°F.



PART NO.	DESCRIPTION	
8.783-040.0	44" with 5000 psi	

# LEGACY SQUARE MOLDED GRIP LANCES



High-quality chrome-plate finish. Solid molded polymer construction and handle with hollow-rib for increased heat dissipation.



- PSI: 5250
- Temperature: 300°F

■ GPM: 12

■ 1/4" Male Inlet and Outlet

PART NO.	DESCRIPTION
8.752-898.0	S Lance, Molded, 12"
8.752-899.0*	S Lance, Molded, 20"
8.752-900.0	S Lance, Molded, 24"
8.752-901.0	S Lance, Molded, 28"
8.752-902.0*	S Lance, Molded, 36"
8.752-903.0	S Lance, Molded, 48"
8.752-904.0	S Lance, Molded, 60"
8.752-905.0*	S Lance, Molded, 79"

\*BENT VERSION AVAILABLE Call representative for pricing and to order.

# LEGACY OVAL MOLDED GRIP LANCES



A comfortable grip reducing fatigue and a stainless-steel or highquality chrome-plated finish. Solid molded polymer construction and handle with hollow-rib for increased heat dissipation.



- PSI: 5250
- Bent or Straight lance options
- Temperature: 300°F
- 1/4" Male Inlet and Outlet

PART NO.	DESCRIPTION
STAINLESS-STEE	L
8.752-882.0	Lance, Molded, 12"
8.752-883.0*	Lance, Molded, 20"
8.752-884.0*	Lance, Molded, 24"
8.904-301.0	Lance, Molded, 24", Bent 15°
8.752-885.0	Lance, Molded, 28"
8.904-302.0	Lance, Molded, 28", Bent 15°
8.752-886.0*	Lance, Molded, 36"
8.904-303.0	Lance, Molded, 36", Bent 15°
8.752-887.0	Lance, Molded, 48"
8.904-304.0	Lance, Molded, 48", Bent 15°
8.752-888.0*	Lance, Molded, 60"
8.752-889.0*	Lance, Molded, 79"
8.904-306.0	Lance, Molded, 79", Bent 15°
CHROME-PLATE	
8.752-890.0	Lance, Molded, 12"
8.752-891.0	Lance, Molded, 20"
8.752-892.0*	Lance, Molded, 24"
8.752-893.0	Lance, Molded, 28"
8.752-894.0	Lance, Molded, 36"
8.752-906.0	Lance, Molded, 36", with handle
8.904-324.0	Lance, Molded, 36", with handle, Bent 15°
8.752-895.0	Lance, Molded, 48"
8.752-907.0	Lance, Molded, 48", with handle
8.752-896.0	Lance, Molded, 60"
8.752-897.0	Lance, Molded, 79"
*BENT VERSION AV	AILABLE Call representative for pricing and to order.

# **STAINLESS STEEL LANCE**

1/2" Hydro Excavating Lances



- Plated Steel
- Temperature: 300°F.
- 1/2" Male Inlet and Outlet

PART NO.	DESCRIPTION
9.118-070.0	60" with 4000 psi
9.118.071.0	72" with 4000 psi



PART NO.	DESCRIPTION
15 DEG BENT	
9.113-700.0	Molded 36" SS 6000 PSI
9.113-701.0	Molded 48" SS 6000 PSI
STRAIGHT	
9.113-704.0	Molded Grip 48" SS Lance 6000 PSI
9.113-705.0	Molded Grip 36" SS Lance, 6000 PSI

# **AP UNINSULATED LANCES**

Stainless-steel or corrosion-resistant, bright zinc-plated lances made with 1/4" high-pressure, lightweight, thin-wall tubing and superior strength rolled threads.

■ PSI: 4100 ■ Temperature: 300°F

PART NO.	DESCRIPTION
STAINLESS-STEE	L
8.710-623.0	Length, 12"
8.710-624.0*	Length, 20"
8.904-285.0	Length 20", Bent 15°
8.710-625.0*	Length, 24"
8.904-286.0	Length 24", Bent 15°
8.710-626.0	Length, 28"
8.710-627.0	Length, 36"
8.710-628.0	Length, 48"
8.710-629.0	Length, 60"
8.710-630.0	Length, 78"
ZINC-PLATED	
8.710-631.0	Length, 12"
8.710-632.0	Length, 20"
8.710-633.0	Length, 24"
8.710-634.0*	Length, 36"
8.710-635.0*	Length, 48"
8.710-636.0	Length, 60"
8.904-297.0	Length 60", Bent 15°
8.710-637.0	Length, 78"
8.904-298.0	Length 78", Bent 15°

\*BENT VERSION AVAILABLE Call representative for pricing and to order.

## **LEGACY VENTED LANCES**

Legacy

Stainless-steel or high-quality chrome-plate finish with molded glass-filled polyamide handle for heat dissipation with hollow insulators for increased heat venting.

	THE NEW STREET, TORS.
■ PSI: 5250	■ 1/4" Male Inlet,

■ Temperature: 300°F

1/4" Female Outlet

PART NO.	DESCRIPTION	
STAINLESS-STEEL		
8.752-868.0	Lance, Vented, 20"	
8.752-869.0	Lance, Vented, 24"	
8.752-871.0	Lance, Vented, 36"	
8.752-872.0	Lance, Vented, 48"	
8.752-873.0	Lance, Vented, 60"	
8.752-874.0	Lance, Vented, 79"	
CHROME-PLATED		
8.752-875.0	Lance, Vented, 20"	
8.752-876.0	Lance, Vented, 24"	
8.752-878.0	Lance, Vented, 36"	
8.752-879.0	Lance, Vented, 48"	
8.752-880.0	Lance, Vented, 60"	
8.752-881.0	Lance, Vented, 79"	

# SUTTNER PUSH AND PULL LANCE



Vented grip can be pushed and pulled up to 90°. For hard to reach applications, such as gutters, fenders, trucks and heavy equipment.



PART NO.	DESCRIPTION
8.710-711.0	ST-85 Push and Pull Lance
8.710-720.0	Handle, Side

# BIG STAINLESS-STEEL LANCES & SIDE HANDLES

For big guns! Complete with an adjustable handle and coupler for 1/4" MPT nozzle and high-pressure stainless-steel pipe.



PART NO.	DESCRIPTION	PSI
8.904-083.0	40" Wand with Handle	4050
8.710-411.0	39", Stainless-steel, 300°F, Inlet 1/2" MNPT, Outlet 1/4" FMPT ST-3600	8700

# **LANCE HANDLES / ACCESSORIES**

Vented grip, side handle with nut, and vented grip with side handle, can be user-attached to uninsulated lances or 1/4" steel pipe. Detachable and reusable!



PART NO.	DESCRIPTION
8.710-717.0	Vent Grip Only (14" long)
8.904-357.0	Grip with Side Handle

# SUTTNER 🥨

PART NO.	DESCRIPTION
8.710-716.0	Vent Grip Only (14" Long) ST-9
8.710-719.0	Grip with Side Handle
8.710-720.0	Side Handle with Nut

# **MV LANCE HANDLE**





- Use On All 1/4" Lances
- Easily Positioned without Removal of Nozzle

PART NO.	DESCRIPTION
8.704-162.0	1/4" Lance Handle

### **GUTTER CLEANER ATTACHMENT**

Easily quick connect to any lance or extension wand to clean gutters or hard to reach areas. The angle improves reach and expands cleaning capabilities. For use with 5.0 or larger nozzle.



- PSI: 3500
- Temperature: 200°F
- Zinc-Plated
- Inlet 1/4" F Socket
- Oulet 1/4" M Plug

PART NO.	DESCRIPTION
8.711-324.0	1/4" Nipple x 1/4" QC

## FIBERGLASS TELESCOPING WANDS

High-quality telescoping wand can reach up to 24' with three sizes to choose from. A lightweight wand that is balanced under pressure.



- PSI: 4000
- GPM: 10.5
- Temperature: 195°F
- 6' 12' Wand Shown





#### **Telescoping Wand**

PART NO.	DESCRIPTION
8.710-589.0	6'-12'
8.710-590.0	6'-18'
8.710-591.0	8-24'
8.700-059.0	Strap and Belt Shoulder Harness
8.711-324.0	Gutter Cleaning Attachment
8.723-896.0	TS12 Replacement Gun
8.710-595.0	TS18 Replacement Gun
8.739-434.0	TS24 Replacement Gun

# SPRAY-FLEX™ FLEX WAND

Access difficult spots easily. Great for cleaning engines, roofs, eaves, or underneath almost anything! Holds its shape under pressure.

- PSI: 3000 or 5000
  - Temperature: 190°F
  - 90° Flexibility
  - 12" 1/4" NPT x 1/4" NPT

PART NO.	DESCRIPTION
8.710-597.0	3000 PSI
8.710-596.0	5000 PSI
8.710-596.0	5000 PSI

### **FLEX LANCES**

Save on broken wand repairs! Flexes a full 180° and returns, preventing bent lances and broken hose. Ideal for self-serve car wash bays.



- PSI: 2500
- Temperature: 200°F
- Industrial-Grade Polyurethane Flex Section
- Galvanized Pipe Ends

PART NO.	DESCRIPTION
8.710-598.0	<b>S</b> 18", 1/4" MPT x 1/4" MPT
8.710-603.0	21", 1/4" MPT x 1/8" FPT
8.710-604.0	24", 1/4" MPT x 1/8" FPT

# **HOBBY GUN, LANCE AND HOSE**

Don't turn away hobby-unit owners. Complete replacement hose, gun and lance.



### Insulated Lance with Gun

- PSI: 4500
- GPM: 8
- Temperature: 320 F
- 3/8" NPT Inlet

#### **Lance with Coupler**

- PSI: 3000
- Temperature: 140 F

#### Lance with 3 Hi/Low Varifan Nozzle

- PSI: 2000
- GPM: 5.5

#### 1/4" x 25" Thermoplastic

- PSI: 3600
- Temperature: 140 F

■ 1/4" QC Brass Socket

■ 1/8" 40x65 brass soap nozzle

■ Weight: 39 oz.

PART NO.	DESCRIPTION
8.754-769.0	Insulated Lance with Gun
8.753-272.0	18" Lance with #3 Hi / Low Varifan Nozzle
8.753-423.0	1/4"x25" Thermoplastic, 22mm both ends
NOTE: See page 14	1 for more Hobby Hose



# **GUN, DUAL LANCE COMBO**

- PSI: 5000
- GPM: 12
- Temperature: 300°F
- Stainless Steel Seat
- 1/4" Stainless Steel Tubes

PART NO.	DESCRIPTION
8.930-771.0	40" with 5000 psi 12 GPM gun



#### **MV925 GUN**

- PSI: 4500
- GPM: 12

PART NO.	DESCRIPTION
8.754-381.0	???

# **LEGACY INDUSTRIAL GUN AND LANCE COMBO**



Gun and lance combo with 36" square-molded grip lance and 1/4" quick coupled socket. Includes nozzle protector.



- PSI: 5000
- GPM: 10.4
- Zinc-Plated Steel Tubes
- Stainless-Steel Seat
- Weight: 39 oz.

PART NO.

#### **DESCRIPTION**

8.904-095.0

■ Temperature: 300°F

Legacy Gun and Lance with 3/8" MPT QC Inlet

## **MV925 GUN AND LANCE COMBO**

Gun and lance combo with pre-assembled 36" square grip lance.



- PSI: 4500
- on Outlet of Lance
- GPM: 8.0
- 1/4" FPT QC Socket Installed 3/8" MPT QC Nipple Installed on Inlet of Gun

PART NO.

8.928-442.0

**DESCRIPTION** MV925 Gun

# **MV925 GUN, LANCE AND HOSE COMBO**

Gun, lance and hose combo with 36" square grip lance and 50' hose.



- PSI: 4000
- 3/8" MPT QC Nipple Installed on Inlet of Gun
- 1/4" FPT QC Socket Installed on Outlet of Lance
- GPM: 8
- R1 4000 PSI 3/8" x 50' Black Hose
- 3/8" FPT QC Sockets Installed on Hose

DESCRIPTION PART NO. 8.928-443.0 MV925 Gun