

4G Mini GPS Tracker

Model: LCA19

LCA19 integrates wireless communication technology and GPS/BDS satellite positioning technology. LCA19I adopts an industrial-grade high-integration full-built-in antenna design. With remote recording, vibration detection, SOS button, WIFI positioning, USB charging, OTA upgrade, overspeed alarm, etc.. With the global positioning service platform, the real-time acquisition, tracking and positioning functions of vehicle data are realized.



MARKET APPLICATIONS







School Kids



Containers



Luxury Vehicles

MAIN FEATURES

5 Modes, smart power saving

Ultra long standby, moving, static, periodical and combines

Waterproof

IP65+, suitable for various scenes usage

Magnetic, no installation needed

Non-slip silicon gel and powerful magnetic, just place and go

GNSS+Wifi location

perform accurate location indoor and outdoor

SOS Button for Emergency

750mah rechargeable li-polymer Battery

>3 years(one position per day)

Multiple Alerts

vibration/low battery/overspeed, etc

Anti-tamper alert

Built-in sensitive light sensor, real-time alert if being removed

Voice Monitoring

OTA Supported



Guangzhou Lotim Technology Co., Ltd.

GSM SPECIFICATIONS

GSM frequency LTE CAT1, FDD: Band 1/3/5/8,

TDD: Band 34/38/39/40/41

GPRS Class 12, TCP/IP

Internal memory 8MB

Phase error RMSPE<5,PPE<20

Max output

FDD-LTE: non-CA Cat1, Max 10Mbps(DL)/Max 5Mbps(UL)

TDD-LTE: non-CA Cat1, Max 10Mbps(DL)/Max 5Mbps(UL)

TDD-LTE: non-CA Cat1, Max 8Mbps(DL)/Max 2Mbps(UL)

Max frequency error ±0.1ppm

Receive sensitivity Class II RBER2%(-102dBm)

GPS SPECIFICATIONS

Chipset AT6558R

RF Channel GPS + BDS

Location accuracy <10 meters

Tracking sensitivity -162dBm

Acquisition sensitivity -148dBm

Avg. hot start≤1sec TTFF (open sky)

Avg. cold start≤32sec

OTHERS

LED indicator GPS(blue), GSM(green), Power(red)

Battery 750mAh/3.7V Li-Polymer Battery

Power Micro USB, 5V/650mA, Fully Recharge: 1.5 Hour

One position per day: 1 year

Standby time Real-time location update: 1week

Vibration update: 1month

Operating temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$

Sensor 3D G-Sensor, Light Sensor

SIM Card Micro SIM

IP Rating IP65(PVC waterproof bag)

Size 62*27*15mm

Weight 50g