


Guangzhou Lotim Technology Co., Ltd.

4G 3CH GPS Dashcam

Model: LCD10

LCD10 is equipped with 3CH cameras, a 4G LTE Cat-4 network, an SOS button, and G-sensors, being the best option for vehicle management. One camera faces the front, one camera towards the cabin, and the left to rear view, keeps recording videos when ACC is on, and even the user could do live streaming video when requested online, assuring this device is always an effective eye for your vehicles.





MARKET APPLICATIONS



Guangzhou Lotim Technology Co., Ltd.

GSM SPECIFICATIONS

| GSM frequency | Version 1: 4G BAND 1/3/5/7/8/20 BAND 38/39/40/41(100Mhz) 3G BAND 1/8, GSM900/1800MHz Version 2: 4G BAND2/4/5/7/28 BAND 38/39/40/41(100Mhz) 3G BAND 2/5, GSM 850/1900MHz |
|-------------------------|--|
| | GPS SPECIFICATIONS |
| Chipset | МТК |
| RF Channel | GPS + BDS |
| Location accuracy | <=5 meters |
| Fracking sensitivity | -162dBm |
| Acquisition sensitivity | -148dBm |
| TTFF (open sky) | Avg. hot start≤1sec |
| | Avg. cold start≤32sec |
| | OTHERS |
| ED indicator | 1 with 4 colors(Green, Red, Blue, Yellow) |
| Norking voltage | 12VDC / 24VDC |
| CPU | MTK8665, Quad-core ARM® Cortex-A53MPCoreTM, operating at 1.5ghz, LPDDR 3 can be up to 3GB, 640 MHz |
| Sensor | TDK40608, 6-axis |
| SIM Card | Micro SIM |
| Storage | 1*TF card (Max. 512G), Format: FAT32, Class 10+ |
| Resolution | Front: 1080P/25FPS, Inner Cabins: 720P/25FPS |
| Server | Up to 2 Servers Connection |
| GPU/RAM/ROM | Dual-core Mali - T720 GPU/1GB/8GB |
| WIFI/BLUETOOTH | 2.4G(802.11b/g/n), BT4.0 |
| Nires | Power +&-, ACC, SOS +&- |
| MIC/SPEAKER | With Micrphone, Speaker: 2W, MAX 90db |
| Buttons | Power, Voice+, Voice - |
| Operating temperature | -20°C~ 70°C |
| | |
| Size | 80mm*60*50mm |

Website: www.lotimcloud.cor

Tel/WhatsApp: +86 15989759137